

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLI
(Other instructions
reverse side)

Form Approved
Budget Bureau No. 42-R142
LEASE DISPOSITION AND REFILL NO.
M. 000085
6 IF INDIAN, A LOTTEE OF TRIBE, NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.

RECEIVED

GAS WELL ☒ OTHER

OF OPERATOR

Service Oil Company

AS OF OPERATOR

1919 - Midland, Texas 79701

Report location clearly and in accordance with an AREA OFFICE

(See page 17 below.)

MAY 13 1975

O. C. C.

AREA OFFICE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Government All

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Under

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 21-T21S-R27

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3236' GR

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 401' Red Bed. Prep to drill ahead. This well was spudded @ 1:00 PM on 5-2-75 and drilled to a T.D. of 401'. Ran 10 Jts. (381.20') 13-3/8" OD 48# H-40 casing set and cemented @ 401' w/450 sacks Class C w/1/4# Flocele, 2% CaCl and 5# Gilsonite/sack cement. Plug down @ 3:30 AM on 5-3-75. Bumped plug w/500# - Held O.K. Cement circulated to surface. WOC 19 Hrs. Tested 13-3/8" casing to 500# for 30 minutes with no drop in pressure.

USGS was notified but did not witness cementing job.

RECEIVED
MAY
U.S. GEOLOGICAL SURVEY
LEGISLATIVE

I hereby certify that the foregoing is true and correct

ORIGINAL SIGNED
BY E. Y. WILDER

TITLE Region Operation Manager

May 6, 1975

(This space for Federal or State office use)

TITLE

DATE

APPROVED
MAY 13 1975
H. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side