

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Hanigan Petr. Corp.</u>		Lease <u>Catchlaw Draw Unit</u>		Well # <u>11</u>	
Location of Well	Unit <u>1955 330 W</u>	Section <u>36</u>	Township <u>21</u>	Range <u>25</u>	County <u>Eddy</u>
Drilling Contractor	<u>Moranco</u>		Type of Equipment <u>Rotary to start approx. 4-18-75</u>		

* Witness

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>20"</u>	<u>16"</u>	<u>65 #</u>		<u>200</u>	<u>circ.</u>
* <u>14 3/4" + 12 1/4"</u>	<u>9 5/8"</u>	<u>36 + 40 #</u>		<u>2300</u>	<u>circ.</u>
<u>8 1/2" + 7 7/8"</u>	<u>5 1/2"</u>	<u>17 + 20 #</u>		<u>11100</u>	

Casing Data: (16 FT K.B TO GL)

INTER Surface 56 joints of 9 5/8 inch 36 + 40 # Grade K-55 NEW LOVE STAR
800 STEEL (Approved) (~~Rejected~~)

Inspected by John Bergstrom date 5-1-75-9⁰⁰ AM

Cementing Program

Size of hole 14 3/4" - 2260' Size of Casing 9 5/8 Sacks cement required 1116 cu/ft

Type of Shoe used GUIDE Float collar used YES Btm 3 jts welded THRED LOK

TD of hole 2260 K.B. Set 2200 Feet of 9 5/8 Inch 36 + 40 # Grade K-55 - 3 CENT.

New-used csg. @ 2260 K.B. with 1447 cu/ft sacks neat cement around shoe - 200 CLASS C. 28 P.A.C.I.
+ 650 sax Howco LITE additives 5 # GILS. 1/4 FLOCELE + 20 P.A.C.I.

Plug down @ 12⁰⁰ NOON (AM) (~~PM~~) Date 5-3-75

Cement circulated YES No. of Sacks 30 CLEAN CMT TO PIT

Cemented by Howco Witnessed by John Bergstrom

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: _____