

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER 110
ARTESTA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Ken R. Bass</u>		Lease <u>Big Eddy Unit</u>		Well # <u>44</u>	
Location of Well	Unit # <u>1980N 6600</u>	Section <u>16</u>	Township <u>21</u>	Range <u>30</u>	County <u>Eddy</u>
Drilling Contractor <u>McVay Drilling Co.</u>			Type of Equipment <u>Rotary</u>		

* witness

APPROVED CASING PROGRAM

Size of Hole <u>24</u>	Size of Casing <u>21"</u>	Weight Per Foot <u>94</u>	New or Used	Depth <u>35</u>	Sacks Cement <u>Red mix</u>
<u>17 1/2</u>	<u>13 3/8"</u>	<u>48</u>		<u>500</u>	<u>525 cin.</u>
<u>12 1/4</u>	<u>9 7/8"</u>	<u>36</u>		<u>3600</u>	<u>925 cin.</u>
<u>8 1/2"</u>	<u>5 1/2</u>	<u>17+20</u>		<u>13500</u>	<u>1000</u>

Casing Data:

^{INTER} Surface 92 joints of 9 7/8 inch 36 # Grade K-55 NEW R3. STEEL
(Approved) (~~Rejected~~)

Inspected by Leon R. Bergstrom date 6-18-75

Cementing Program

Size of hole 12 1/4 Size of Casing 9 7/8 Sacks cement required 1135 cu/ft.

Type of Shoe used GUIDE Float collar used YES Btm 3 jts welded THREADED

ID of hole 3560 Set 3574 Feet of 9 7/8 Inch 36 # Grade K-55 STEEL

New-used csg. @ 3560 OK with 100 sacks neat cement around shoe 2 1/2 CASH
+ 1800 sax Howco LITE additives 18% SALT 1/4" FLOCCULE

Plug down @ 8 50 (AM) (~~PM~~) Date 6-18-75

Cement circulated YES No. of Sacks 150 SX

Cemented by Howco Witnessed by Leon R. Bergstrom

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: