ED STATES

SUBMIT IN TRL

Copy to St Form approved.

		Budge	t Bure	au N	0. 4	2R	142	i
5.	LEASE	DESIG	NATION	AND	SER	IAL	NO.	
		٠ ١	7	2.			منہ	

DEPAR	5. LEASE DESIGNATION AND SERIAL NO.		
	-21-011-266 NM-12241		
	DTICES AND REPORTS (posals to drill or to deepen or plug l GATION FOR PERMIT—" for such p		G. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS OTHER		OCT 1.8 1978	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Cities Service Compan	y /		8. FARM OR LEASE NAME Little Box Canyon Unit
3. ADDRESS OF OPERATOR P.O. Box 1919 Midla:	nd, TX 79702	ARTESIA, OFFICE	9. WELL NO. 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
4. LOCATION OF WELL (Report location See also space 17 below.) At surface	10, FIELD AND POOL, OR WILDCAT Will Strawn		
Eddy County, New Mexi	of Section 7, T-21S,	R-22E,	Sec 7, T=21S, R-22E
14. PERMIT NO.	15. ELEVATIONS (Show whether DE 4411' DF	F, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE - New Mexico
16. Check	Appropriate Box To Indicate N		ក្រុម គឺ និទី គឺ និទី B M
NOTICE OF INT	ention to:	SUBSEQ	QUENT REPORT OF S
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE	MULTIPLE COMPLETE ABANDON*	WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (Other)	REPAIRING WELL ALTERING CASING ABANDONMENT
REPAIR WELL	CHANGE PLANS	(Utiler)	

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 8350', PB 8274'

Recomplete in Strawn

REPAIR WELL

- MIRU pulling unit. Kill well w/2% KCL water. Install BOP and pulliting & packer.
- Set CIBP at approximately 7925' and dump 35' cmt on top.
- GIH with open ended the and spot Acetic across interval 7350-7250
- Perforate Strawn SS 2 shots/ft at each of the following intervals 342 7343 7344', 7345', and 7346' using 4" Hyper Jet II csg gun w/0.40" holes & 23.07" penetration.
- RIH w/Loc-Set packer and quick flow nipple on 2-7/8" tbg & set at approximately 7290'. Drop bar to rupture disc and test well natural.
- 6. If necessary, acidize strawn perfs 7342-7346'.
- Backflow load and test.
- Run 4-point test.

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

		· 원인하레인 원회 종 <u>립송화</u> 년
S. I hereby certify that the foregoing is true and correct	Paris on Organition - M	200 70 70: 3
SIGNED	TITLE Region Operations Mgr	DATE 10-10-70
(This space for Federal of State office use) APPROVED BY TOP	TITLE ACTING DISTRICT ENGINEER	OCT 16 1978
CONDITIONS OF APPROVAL, IF ANY:		