

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

SEP 25 1975

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. K-6364
7. Unit Agreement Name
8. Farm or Lease Name State CS
9. Well No. 1
10. Field and Pool, or Wildcat Und. Burton Flat Mor.
12. County Eddy

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

O.C.C.

ARTESIA, OFFICE

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER: Dry Hole
2. Name of Operator Cities Service Oil Company
3. Address of Operator Box 1919 - Midland, Texas 79701
4. Location of Well UNIT LETTER L 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 17 TOWNSHIP 21S RANGE 27E N.M.P.M.
15. Elevation (Show whether DF, RT, GR, etc.) 3233' DF

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPERATIONS ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 11,557' Sand & Shale PBD 11,255'. We propose to plug and abandon this well in the following manner:

1. MIRU casing puller, shoot 5-1/2" csg. @ approx. 10,250' and pull casing.
2. Displace a 40 sack cement plug 1/2 in and 1/2 out of 5-1/2" casing stub @ approx. 10,300 - 10,200'.
3. Displace a 40 sack cement plug across top of Canyon @ approx. 9865 - 9765'.
4. Displace a 40 sack cement plug across top of Wolfcamp @ approx. 8825 - 8725'.
5. Displace a 40 sack cement plug across top of 2nd Bone Springs Sand @ approx. 7100-7000'.
6. Displace a 40 sack cement plug across top of 1st Bone Springs Sand @ approx. 6350-6250'.
7. Displace a 40 sack cement plug across top of Bone Springs @ approx. 5025 - 4925'.
8. Displace a 40 sack cement plug 1/2 in and 1/2 out of 9-5/8" casing shoe @ approx. 3025 - 2925'.
9. Set a 10 sack cement surface plug in top of 9-5/8" csg. @ approx. 58 - 0' and install a 4" dry hole marker.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED E. Spiller TITLE Region Operation Manager DATE Sept. 24, 1975

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE SEP 25 1975

CONDITIONS OF APPROVAL, IF ANY:

Intervals between plugs filled w/ mud

Notify N.M.O.C.C. in sufficient time to witness

Spotting plugs