

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

AUG 21 1975

For 10-13
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Type of Lease	State <input type="checkbox"/> Fed <input checked="" type="checkbox"/>
State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG A WELL TO A DEEPER WELL. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Cities Service Oil Company	8. Ives A Com.
3. Address of Operator Box 1919 - Midland, Texas 79701	9. 1
4. Location of Well UNIT LETTER J 1980 South 2190 East 30 21S 27E	10. Wildcat Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3116' GR(Est.)	11. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data.

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated completion date and proposed work) SEE RULE 1103.

T.D. 418' Sand and Anhydrite. Prep to drill ahead. This well was spudded @ 8:30 AM on 8-16-75 and drilled to a T.D. of 418'. Ran 9-1/2 Jts. (398.20') 13-3/8" OD 48# H-40 casing set and cemented @ 418' w/450 sacks Class C w/2% CaCl cement. Plug down @ 11:30 PM on 8-17-75. Bumped float w/900# - Held O.K. Cement did not circulate. WOC 7 hrs. Ran Temp. Survey. Top of cement @ 80'. Ran 1" tubing in annulus and cemented as follows:

50 sacks Class C w/4% CaCl. WOC 2 hrs. Tagged cement @ 56'. 24' fill.
75 sacks Class C w/4% CaCl. WOC 2 hrs. Tagged cement @ 48'. 8' fill.
175 sacks Class C w/4% CaCl. Cement circulated to the surface...

WOC 5 hrs. Total WOC time of 12 hrs. Tested 13-3/8" casing to 750# for 30 minutes with no drop in pressure.

NMCCC representative notified but did not witness cementing job.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Ephraim TITLE Region Operation Manager August 19, 1975
APPROVED BY For Record Only TITLE SUPERVISOR, DISTRICT II AUG 26 1975
REMARKS OF APPROVAL, IF ANY: