NEW MEXICO OIL CONSERVATION COMMISSION DRAWER DD ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

operator Fenise of				llied-Com.			Well #	2
Location of Well				Township 20		Range 27	County	y
Drilling Contractor WEK			Rotory & Start apport, 7-15-75					
4/2" must be a must be tied of Size of Hole	mented be	APPROVEI Surface	D CASI	NG PROG	GRAM	Capetan	foy encou	ntered
Size of Hole	e Size of Casing		Weight Per Foot		New	or Used	Depth	Sacks Ceme
11	879"		Jy				1100	Cire.
7%"	47	/2	9,50				3000'	250
	244 11							
Casing Data:								
Surface joints of inch # Grade								
(Approved) (Rejected)								
Cementing Program Size of hole 11 Size of Casing 3 Sacks cement required 285 Coff								
Type of Shoe used Float collar used Btm 3 jts welded TD of hole 1/28 Set Feet of Inch # Grade								
New-used csg. @ with sacks neat cement around shoe								
+saxadditives								
Plug down @					·	·		, Þ
Coment circulated No. of Sacks								
Cemented by Witnessed by Temp. Survey ran @ (AM) (PM) Date top cement @								
Temp. Survey ran @ (AM) (PM) Date top cement @ Casing test @ (AM) (PM) Date								
Method Used Witnessed by								
Checked for shut off @ (AM) (PM) Date								
Method used Witnessed by								
Remarks: ARRIVED LOCATION @1 AM 7-7-75. CREW WAS ABOUT 5 JOINTS OF								
8% OFF T.	D. Tool	PUSHER LA	ARRY ,	ARHOLI	WA	S SPU	DDING	CASING 1
A VERY A	BUSIVE	MANNER	INA	MATT	6741	PT TO C	GET IT	THRU SOM
BRIDGED 1+	OLE. A)	FTER SPU	DDIN	G FOR	HPP	Rox 4h	rs. HE	HAD ABOUT
3 JOINTS	IETTO	GO. WHE	M 7H	C 8%	XZ	SWED	SE BRO	KE. I LEF
THE RIG AT		4 7-7-75	706	O AND	wi	THESS	M ICME	SURVEY.OF
ANOTHER WE IT WAS LAD	ter la	GRNED TH	IEY K	HAD C	EME	NTED K	VITHOUT,	NOTIFYING
THE O.C.C. C		4	,		4		110/20	,