

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	☒
FILE	☒
U.S.G.S.	
LAND OFFICE	
OPERATOR	☒

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

O. C. D.
ARTESIA OFFICE

Form C-103
Revised 10-1

5a. Indicate Type of Lease

State ☒

Fed ☐

5. State Oil & Gas Lease No.

K-4397

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☐ GAS WELL ☐ OTHER Depleted Gas Well	7. Unit Agreement Name -----
2. Name of Operator Penroc Oil Corporation	8. Firm or Lease Name Allied Comm.
3. Address of Operator P. O. Drawer 831, Midland, Texas 79702	9. Well No. 2
4. Location of Well UNIT LETTER <u>B</u> <u>1160</u> FEET FROM THE <u>North</u> LINE AND <u>1830</u> FEET FROM THE <u>East</u> LINE, SECTION <u>27</u> TOWNSHIP <u>20S</u> RANGE <u>28E</u> NMPM.	10. Field and Pool, or Wildcat Penlon Delaware
15. Elevation (Show whether DF, RT, GR, etc.) 3259 GL 3269 KB	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

REMEDIAL WORK ☐

ALTERING CASING

TEMPORARILY ABANDON ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT

PULL OR ALTER CASING ☒

CHANGE PLANS ☐

CASING TEST AND CEMENT JQB ☐

OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Total Depth - 2835' Perfs: (Delaware Sd) 2745-2775' & 2788-2810'
Top Delaware Sd. 2369' 8 5/8" csg. @ 1017' w/cement to surface.
4 1/2" csg. @ 2835' with top cement @ 1230' by temp. Svy.

- Propose:
- 1.) Set CIBP @ 2700', above perfs. Bailer dump 35' cement plug on top.
 - 2.) Cut off 4 1/2" csg. @ 1050' and pull.
 - 3.) Set cement plug of 150' in and out of 4 1/2" csg. stub and in 8 5/8" csg. 1100' up to 950'.
 - 4.) Set 25' cement plug in top of 8 5/8" csg and install dry hole marker.
 - 5.) Level and clean location.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE President

DATE 10/31/84

Original Signed By
Mike Williams

APPROVED BY

Oil & Gas Inspector

TITLE

DATE

NOV 2 1984

CONDITIONS OF APPROVAL, IF ANY

Notary Public, O.C.D. in sufficient time to witness

Plugging