

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	1
U.S.G.S.	
LAND	
FILE	
OPER	OR

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-60

RECEIVED

SEP 12 1975

5a. Indicate Type of Well State <input checked="" type="checkbox"/> Free <input type="checkbox"/>
5. State Oil & Gas Lease No. K-5115
7. Unit Agreement Name
8. Farm or Lease Name Stonewall EP State
9. Well No. 1
10. Field or Pool, or Wildcat Wildcat Morrow
12. County Eddy

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT DEPTH OR TO USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

B. B. C.  
ARTESIA, OFFICE

1. Name of Operator Yates Petroleum Corporation	2. Name of Operator Stonewall EP State
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER F, 1980 FEET FROM THE North LINE AND 1980 FEET FROM THE West LINE, SECTION 30 TOWNSHIP 20S RANGE 28E NMPM.	10. Field or Pool, or Wildcat Wildcat Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 3282' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER Set 5 1/2" Production Casing <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated work) SEE RULE 1103. *DD 11478*

Ran 12 joints 5 1/2" 20#, K-55 LT&C (503'), 249 joints 5 1/2" 17#, K-55 LT&C (10540'), 10 joints 5 1/2" 20# K-55 LT&C (399') (Total 11442'), Float shoe at 11433; Float Collar at 11380', 10 centralizers, DV Tool at 9186'. Cemented w/500 gallons mud flush, 125 sacks Hali-Lite, 275 sacks Class "H" 0.6% CFR-2 and 5# KCL, displaced w/fresh water below DV Tool. PD 2:30 PM 8-31-75. Opened DV Tool and circulated 5 hours. Cemented 2nd Stage w/500 gallons mud flush, 775 sacks Hali-Lite and 125 sacks Class "H" w/0.6% CFR-2, and 5# KCL, displaced hole w/fresh water. Bumped plug to 3200#. OK. PD 9:30 PM 8-31-75. WOC 10 hours and ran Temperature Survey, found top of cement outside casing at 4800', inside casing at 9080', set slips, cut off casing. WOC. Tested casing to 1500# for 30" OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief

SIGNED Christie Tomlinson TITLE Geol. Secty 9-11-75  
APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE SEP 16 1975  
CONDITIONS OF APPROVAL, IF ANY: