UNITED STATES
DEPARTMENT OF THE INTERIO
GEOLOGICAL SURVEY

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-0557562
C/SF GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME RECEIVED
SUNDRY NOTICES AND DEPORTS ON WELLS	7. UNIT AGREEMENT NAME
SUNDRY NOTICES AND REPORTS ON WELLS	≥ • • • · · · · · · · · · · · · · · · ·
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME SEP 4 198
1. oil gas	Wright-Federal:
well well other Depleted Gas Well	9. WELL NO.
2. NAME OF OPERATOR	1 ARTESIA, OFFICE
Penroc Oil Corporation	10. FIELD OR WILDCAT NAME Angell
3. ADDRESS OF OPERATOR	Ranch Atoka Morrow (Gas)
P. O. Drawer 831, Midland, Texas 79702-0831	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA FREE A FREE FREE FREE FREE FREE FRE
below.) 1980' fEL, 660' fSL	6-20S-R28E
AT SURFACE:	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Eddy New Mexico
AT TOTAL DEPTH:	14. API NO.
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	30-015-21580
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
SCOURCE FOR ADDROVAL TO	3323 GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
FRACTURE TREAT	ARCH SEE CARRES
SHOOT OR ACIDIZE	그러워티 - 기원에 취임점점
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING X DEP 1 191	
MULTIPLE COMPLETE	Y (프로마 - 항상활성 - 원 등록성본 - 및 - H
ABANDON* X	
other)	SHRVEY IN THE STORY OF A BUILDING
woswes, cow w	
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is di measured and true vertical depths for all markers and zones pertinent	roctionally drilled give exhausteen teresteen a
8-28-81 T.D 11,160' P.B.T.D 10,980'	tto this work.)
Plan to:	
1. Set C.I.B.P. @ 10,700' w/50' cement pl	lug on top. Will be above
Morrow perfs 10,828'-10,894'.	rug on cop. will be anove.
2. Set 100' cement plug 9,445'-9,345' (Ac	rose top of Strawn)
3. Cut off 4 1/2", 11.60#, N-80 casing at	approx 8:700' and pull
4. Set 708 / 20ment plug 8,750'-8,650' (36	Fin and out of 4 1/2" geg stub
5. Set " " 4,312'-4,212' (Ac	cross top of Bone Spring).
6. Set " " 2,550'-2,450' (50	of in and out of 8 5/8" casing
bo	ottomed @ 2,500 %) 2 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3 3
Set 100' cement plug 935' 835' (Yates	
. set " " 190'-200' Sait	and the control of th
7. Set 15 sack cement plug in top of 8 5/	그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그 그
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	불어 들고 그리 그 글은 사람이
GIGNED AS AMENDED	DATE <u>8-28-81</u>
(This space for Federal or State office	
The state of the s	e use)
(Org. Sgd.) PETER W. CHESTER	

JAMES A. GILLHAM DISTRICT SUPERVISOR

*See Instructions on Reverse Side