N. T.

Form 9-331 Dec. 1973 UNITED STATES		Form Appro	ved. sau Ng; 42-R1424	
UNITED STATES	5. LEASE		ភ្នំ ក ក	
DEPARTMENT OF THE INTERIOR 08270	NM-0557562			`
GEOLOGICAL SURVEY	6. IF INDIAN, ALL	OTTEE OR T	RIBE NAME	
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEM	NT NAME	REC	EIVED
eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEAS Wright Fede		2.3 % > 0 Ph	0.400
1. oil gas other Depleted Gas well other	9. WELL NO.	3 3 3 3	SEP	9 1982
2. NAME OF OPERATOR	1 2	5 2 K	ું <u>૦</u> . (
Penroc Oil Corporation / 3. ADDRESS OF OPERATOR	10. FIELD OR WILD Angell Rang			OFFICE
P. O. Drawer 831, Midland, Texas 79702	11. SEC., T., R., M.	* 	·	
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA :	i ő B	\$7.50 \$7.50	
AT SURFACE: 1980' fEL, 660' fSL	12. COUNTY OR PA	RISH 13.		-
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:		New	Mexico	-
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	14. API NO. 30-015-215	3 4		
REPORT, OR OTHER DATA	15. ELEVATIONS (KDB. AND WD	-)
DECUTET FOR APPROVAL TO	3323 GR 😘	339 KB		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	o C	7 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	+ 25 + 25 + 25 + 25 + 25 + 25 + 25 + 25	
FRACTURE TREAT	950752501 8		2000 2000 2000 2000 2000 2000 2000 200	
SHOOT OR ACIDIZE			# 7 6 mm	
REPAIR WELL PULL OR ALTER CASING E S S S S S S S S S S S S	(NOTE: Report result	s of multiple oran 9–330.)?	completion or zone	
MULTIPLE COMPLETE	1907 323			
CHANGE ZONES	og og var ∤ verstag			:
(other)				
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinent	irectionally drilled, given to this work.)*	ve subsurfa	pertinent dates	i
1. 3-17-82 Set bridge plug @ 10,700' w/50' c	ement plug on	top;		
2. " Set 100' cement plug 9445-9345' a 3. 3-18-82 Cut off 4½", 11.60#, N-80 csg @ 8	702' Pulled	ciami.	ေသာက္သည္။ ကြည္သည္	
4. 3-20-82 Set 150' cement plug 8775-8625' i	n and out of 4	t csg	stub,	
5. " Set 100' cement plug 4312-4212'ac	ross top Bone	Spring.	មន្ត្រីឡើ	
6. " Set 100' cement plug 2550-2450'. set at 2500')				
7. " Set 15 sack cement plug in top of	8 5/8" csg. w	/dry ho	le marker	
in place	9			
Will advise when surface stipulat	ions have been	met for	r final	
inspection & approval.	្ន ១.ប	ကြောင်း ကြောင်းကြောင်း ကြောင်းကြောင်း	14 de 15 de	
	ે છ ે.		97.5 97.5 97.5	
Subsurface Safety Valve: Manu. and Type		_ \$# @	្តីខ្លួំ ទី គ្នា ក្រុស ក្នុង	:.
18. I hereby certify that the foregoing is true and correct	(†) (5) (4) (8)	5	262° 69 2 428 03 2 438 03 2 438 03 3 438 03 4 438 03 4 438 03 4 438 03 5 5 6 6 6 5 6	
SIGNED TITLE President		3-82	3 3 3 3	-
(This space for Federal or State off	ice use)			•
APPROVED BY TITLE TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE	APP	ROVED	-
*See Instructions on Reverse S		SEP AAI	8 1982	
	1 7		A. GILLHAM SUPERVISOR	