	U TED STAT		SUBMIT IN TR CAT (Other instruct. on	re-	Form apj Budget E ASE DESIGNAT	ureau No.	. 42-R1424. EELAL NO.
orm		INTERIOE	TOTES AIDA)	5. LE	ASE DESIGNAT	NON AND E	ERIAL NO.
	PARTMLIT OF THE		V VEIBE BLUE/	1		- ·	
GEOLOGICAL SURVEY					IM-2548		RIBE NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT-" for such proposals.)							• • •
(Do not use this form t Use	for proposals to drill or to deep "APPLICATION FOR PERMIT-	en or plug back -" for such propos	to a different reservoir. sals.)	-		-	
<u></u>	······································			7. 03	IT AGREEMEN	T NAME	
OIL GAS WELL OTHER							
2. NAME OF OPERATOR				1	8. FARM OF LEASE NAME Roc Federal		
MOTTIS R	. Antweil 🗸				LL NO.		
• • • •	, Hobbs, New Me	vico 882	40	-			
. LOCATION OF WELL (Report	location clearly and in accordan	ice with any Stat	te requirements.•	10. F	LIELD AND POO	L, OR WIL	DCAT
See also space 17 below.) At surface					Avalon		<u>د آرا</u>
1980' FW	L & 660' FSL, Se	c. 4-T21	S-R26E	11. 8	SUBVET OR	OR BLE. A	ND
1900 14.					4-T21S-	R26E	
4. PERMIT NO.	15. ELEVATIONS (Sho	w whether DF BT	GR etc.)	12. 0	OUNTY OR PA	RISH 13.	STATE
a andria au.	3202 '				Eddy		w Mex
			() I D			-	. v
	heck Appropriate Box To	Indicate Natu					·
NOTICE	OF INTENTION TO:		SUB	SEQUENT BI	PORT OF:		-
TEST WATER SHUT-OFF	PULL OR ALTER CASING		WATER SHUT-OFF	X	REPAIRI	NG WELL	
FRACTUBE TREAT	MULTIPLE COMPLETE		FRACTURE TREATMENT		1	G CASING	· · · · ·
SHOOT OR ACIDIZE	ABANDON* CHANGE PLANS		SHOOTING OR ACIDIZING	L	ABANDO	NMENT*	
(Other)	CHANGE PLANS		(Note: Report res	ults of mu	tiple complet	lon on W	ell -
proposed work. If well nent to this work.)* Spudded 350'. Ce	9:00 A.M. 17 Jul mented 13-3/8" c	bourface locations Ly, 1975. Casing @	Completion or Reco stalls, and give pertinent da and measured and true ver Drilled 17- 350' with 200	ttes, includ rtical depti 1/4" sx H	hole to	date of a rkers and	tarting án zones perti
proposed work. If well Spudded 350'. Ce cement c 2% CaCl2 annular cement.	<pre>is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" c ontaining 1/4 lk . Top of cement space with 19 yc Plug down 2:15</pre>	bourface locations casing @ c/sx. Flo t 236'. ls of gra PM 18 Ju	Completion or Reconstants, and give pertinent data and measured and true version of the second secon	1/4" sx H gils entin c 24	hole to alcolit onite a g of ready-n hrs. Te	date of a rkers and 	
proposed work. If well Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 1k . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30	ly, 1975. casing @ o/sx. Flo t 236'. ls of gra PM 18 Ju min with	Completion or Reconstants, and give pertinent data and measured and true version of the second secon	1/4" sx H gils entin c 24	hole to alcolit onite a g of ready-n hrs. Te	date of a rkers and 	
proposed work. If well Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w	<pre>is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" c ontaining 1/4 lk . Top of cement space with 19 yc Plug down 2:15</pre>	ly, 1975. casing @ o/sx. Flo t 236'. ls of gra PM 18 Ju min with	Completion or Reconstants, and give pertinent data and measured and true version of the second secon	1/4" sx H gils entin c 24	hole to alcolit onite a g of ready-n hrs. Te	date of a rkers and 	
proposed work. If well Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 1k . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30	ly, 1975. casing @ o/sx. Flo t 236'. ls of gra PM 18 Ju min with	Completion or Reconstraints, and give pertinent dates and measured and true version of the second se	1/4" sx H gils entin s of C 24 n pre	hole to alcolit onite a g of ready-n hrs. Te ssure.	date of a rkers and ce and mix ested	
proposed work. If well Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 lk . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30 g ahead w/ 12-1/4	ly, 1975. casing @ c/sx. Flo t 236'. ls of gra PM 18 Ju min with 4" bit.	Completion or Reconstraints, and give pertinent dates and measured and true version of the second se	1/4" sx H gils entin s of C 24 n pre	hole to alcolit onite a g of ready-n hrs. Te ssure.	date of a rkers and ce and mix ested	
proposed work. If well Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 lk . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30 g ahead w/ 12-1/4	ly, 1975. casing @ o/sx. Flo t 236'. ls of gra PM 18 Ju min with	Completion or Reconstraints, and give pertinent dates and measured and true version of the second se	1/4" sx H gils entin s of C 24 n pre	hole to alcolit onite a g of ready-n hrs. Te ssure.	date of a rkers and ce and mix ested	
proposed work. If well Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 lk . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30 g ahead w/ 12-1/4	Ly, 1975. casing @ o/sx. Flo t 236'. ls of gra PM 18 Ju min with 4" bit. ECE	Completion or Reconstraints, and give pertinent dates and measured and true verses of the second sec	1/4" sx H gils entines of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and and nix ested	
proposed work. If well Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 lk . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30 g ahead w/ 12-1/4	ly, 1975. casing @ c/sx. Flo t 236'. ls of gra PM 18 Ju min with 4" bit.	Completion or Reconstraints, and give pertinent dates and measured and true verses. Drilled 17-350' with 200 Docele, 5 lb/Bx Completed cem avel and 32 yd aly, 1975. Wo on no decline i VED 1975	1/4" sx H gils entin s of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and te and nix ested	
proposed work. If well Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 lk . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30 g ahead w/ 12-1/4	JUL 2 3	Completion or Reconstraints, and give pertinent dates and measured and true verses. Drilled 17-350' with 200 Docele, 5 lb/Bx Completed cem avel and 32 yd aly, 1975. Wo on no decline i VED 1975	1/4" sx H gils entin s of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and te and nix ested	
proposed work. If well Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 lk . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30 g ahead w/ 12-1/4	JUL 2 3	Completion or Reconstraints, and give pertinent dates and measured and true verses. Drilled 17-350' with 200 Docele, 5 lb/Bx Completed cem avel and 32 yd aly, 1975. Wo on no decline i VED 1975	1/4" sx H gils entin s of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and te and nix ested	
proposed work. If well Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 lk . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30 g ahead w/ 12-1/4	JUL 2 3	Completion or Reconstraints, and give pertinent dates and measured and true verses. Drilled 17-350' with 200 Docele, 5 lb/Bx Completed cem avel and 32 yd aly, 1975. Wo on no decline i VED 1975	1/4" sx H gils entin s of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and te and nix ested	
proposed work. If well nent to this work.)* Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w Drilling	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 lk . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30 ahead w/ 12-1/4	JUL 2 3	Completion or Reconstraints, and give pertinent dates and measured and true verses. Drilled 17-350' with 200 Docele, 5 lb/Bx Completed cem avel and 32 yd aly, 1975. Wo on no decline i VED 1975	1/4" sx H gils entin s of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and te and nix ested	
Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w Drilling	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 1k . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30 ahead w/ 12-1/4 R	Ly, 1975. casing @ o/sx. Flo t 236'. ds of gra PM 18 Ju min with 4" bit. ECEL JUL 2 3 D.C. ARTESIA. C	Completion or Reconstraints, and give pertinent dates and measured and true verses. Drilled 17-350' with 200 Docele, 5 lb/Bx Completed cem avel and 32 yd aly, 1975. Wo on no decline i VED 1975	1/4" sx H gils entin s of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and ce and nix ested	
Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w Drilling	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 1k . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30 ahead w/ 12-1/4 R	Ly, 1975. Casing @ o/sx. Flo t 236'. ls of gra PM 18 Ju min with 4" bit. ECEI JUL 2 3 D.C. ARTESIA. C	Completion or Reconstraints, and give pertinent data and measured and true verses of the second seco	1/4" sx H gils entin s of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and ce and nix ested	
Spudded Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w Drilling 8. I hereby certify that the fr	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 1k . Top of cement space with 19 yo Plug down 2:15 7/500 psi for 30 ahead w/ 12-1/4 R	Ly, 1975. casing @ o/sx. Flo t 236'. ds of gra PM 18 Ju min with 4" bit. ECEL JUL 2 3 D.C. ARTESIA. C	Completion or Reconstraints, and give pertinent data and measured and true verses of the second seco	1/4" sx H gils entin s of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and ce and nix ested	
 proposed work. If well nent to this work.)* Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w Drilling 8. I hereby certify that the formation of the space for Faderal of the space for fadera of the space of the space for fadera of the space of	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 lk . Top of cement space with 19 you Plug down 2:15 7/500 psi for 30 ahead w/ 12-1/4 R oregoing is true and correct tay office use)	Ly, 1975. casing @ o/sx. Flo t 236'. ds of gra PM 18 Ju min with 4" bit. ECEL JUL 2 3 D.C. ARTESIA. C	Completion or Reconstraints, and give pertinent data and measured and true verses of the second seco	1/4" sx H gils entin s of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and ce and nix ested	
 proposed work. If well nent to this work.)* Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w Drilling 8. I hereby certify that the formation of the space for Faderal of the space for fadera of the space of the space for fadera of the space of	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 lk . Top of cement space with 19 you Plug down 2:15 7/500 psi for 30 ahead w/ 12-1/4 R oregoing is true and correct 	Ly, 1975. Casing @ o/sx. Flo t 236'. ls of gra PM 18 Ju min with 4" bit. ECEL JUL 2 3 D.C. ARTESIA. C	Completion or Reconstraints, and give pertinent data and measured and true verses of the second seco	1/4" sx H gils entin s of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and ce and nix ested	
 proposed work. If well nent to this work.)* Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w Drilling Is. I hereby certify that the formation of the space for Faderal of the space for fadera of the space of the space for fadera of the space of the space	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 lk . Top of cement space with 19 you Plug down 2:15 7/500 psi for 30 ahead w/ 12-1/4 R oregoing is true and correct tay office use)	Ly, 1975. Casing @ o/sx. Flo t 236'. ls of gra PM 18 Ju min with 4" bit. ECEL JUL 2 3 D.C. ARTESIA. C	Completion or Reconstraints, and give pertinent data and measured and true verses of the second seco	1/4" sx H gils entin s of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and ce and nix ested	
proposed work. If well nent to this work.). Spudded 350'. Ce cement c 2% CaCl2 annular cement. casing w Drilling II. I hereby certify that the for SIGNED	is directionally drilled, give sub 9:00 A.M. 17 Jul mented 13-3/8" of containing 1/4 lk . Top of cement space with 19 yd Plug down 2:15 7/500 psi for 30 ahead w/ 12-1/4 R oregoing is true and correct VAL, IF ANY:	Iy, 1975. Casing @ o/sx. Flo t 236'. Is of gra PM 18 Ju min with 4" bit. ECEL JUL 2 3 D.C. ARTESIA. C NITLE Agu	Completion or Reconstraints, and give pertinent data and measured and true verses of the second seco	1/4" sx H gils entin s of c 24 n pre	hole to alcolit onite a g of ready-r hrs. Te ssure.	date of a rkers and ce and nix ested	