

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TR
(Other instruct.
verse side)DATE*
ON re-Form approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-25847

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.

RECEIVED

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Morris R. Antweil

3. ADDRESS OF OPERATOR

Box 2010, Hobbs, New Mexico 88240

O. C. C.
ARTESIA, OFFICE4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

660' FSL & 1980' FWL Sec. 4-T21S-R26E

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Roc Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Avalon

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

4-T21S-R26E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 12-1/4" hole to 2570'. Cemented 64 jts. (2579.84')
 24, 28 & 32# J-55 8-5/8" casing @ 2570'. with 800 sx. Halcolite
 Cement containing 1/4#/sx. Flocele, 5#/sx gilsonite, & 10#/sx
 salt followed by 200 sx. Class "C" cement w/2% Ca Cl₂. Circulated
 approximately 120 sx. cement. Plug down 8:00 AM 23 Jul, 1975.
 WOC 18 hrs. Tested 8-5/8" casing w/1200 psi-no decline in pressure
 in 30 mins. Drilling ahead with 7-7/8" bit.

18. I hereby certify that the foregoing is true and correct

SIGNED

R M Williams

TITLE

Agent

DATE July 24, 1975

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

JUL 28 1975

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

*See Instructions on Reverse Side

APPROVED
JUL 23 1975
K. L. BEEKMAN
ACTING DISTRICT ENGINEER