

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instructions on
reverse side)Form approved
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-0489599

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

2310' FSL & 660' FEL of Sec. 13-21S-26E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3220' GR

UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

ARCO "EI" Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 13-21S-26E
Unit I NMPM

12. COUNTY OR PARISH

Eddy

13. STATE

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set Production casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 11554'; PBTD 11536'. Ran casing as follows: 14 joints 5½" 20# K-L (589'), 238 joints 5½" 17# K-L (10453'), 11 joints 5½" 20# K-L (481'), 263 joints 5½" casing (11523') set at 11536' KB. Cemented w/500 gallons mud flush, 235 sacks Class "H" w/3/4% CFR-2 and 5# KCL, displaced w/40 bbls of 2% KCL and 226 bbls fresh water. PD 6:50 PM 9-15-75. Tested casing and plug to 2000 psi. OK. Ran Temperature Survey and found top of cement at 10520' KB.

RECEIVED

SEP 17 1975

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Eddie L. Beckman

TITLE

Engineer

DATE

9-17-75

(This space for Federal or State office use)

APPROVED BY:

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side