

EDDY COUNTY (Cont'd)

PENROC OIL CORP.

1 JCW State

API 30-015-21604

WINCHESTER (MRRW): (8-18-75); 11,400' RT; Sec 2-20s-28e; 660' FSL 1980' FEL Sec; D
10 mi N 8 4 mi E/Carlsbad; Elev 3272' CL; Spud 8-19-75; 13-3/8" 400'/350 sx; 8-5/8"
2701'/1000 sx; DST (Delaware) 3295-3400', op 1 hr, rec 260' SW w/tr oil, 1 hr ISIP
1445#, FP 106-133#, 1 hr FSIP 1419#, HP 1550-1550#, BHT 100 degs; DST (U/Mrrw)
10,985-11,160', op 1 hr, rec 200' SW, 1 hr ISIP 3414#, FP 393-437#, 1 hr FSIP 1421#, HP 5660-5638#, BHT 170 degs; DST
(L/Mrrw) 11,248-270', op 3 hrs 30 mins, GTS in 7 mins @ 59,000 CFGPD incr to 394,000 CFGPD @ end of test, rec 70'
slit GCM, 1 hr ISIP 4558#, FP 46-92#, 6 hr FSIP 4558#, HP 5765-5720#, BHT 175 degs; 4-1/2" 11,339'/575 sx; C/W.E.K.
Drig.; SP-DST (Canyon Lm) 9935-66', pkr failed; Log Tops: Delaware Sand 2890', Bone Spring 4704', First Bone
Spring Sand 6522', Second Bone Spring Sand 7160', Third Bone Spring Sand 8475', Wolfcamp Lime 9077', Canyon Lm
9914', Strawn Lm 10,115', Morrow Sh 10,981', Barnett 11,302'; Perf (Morrow) 11,240-250' w/2 SPF; Acid (11,240-250')
3000 gals; Flwd 377,000 CFGPD w/tr wtr thru 3/4" chk, TP 11# (11,240-250'); Frac (11,240-250') 30,000 gals + 33,000#
sd; Flwd 435,000 CFGPD thru 3/4" chk/24 hrs, TP 15# (11,240-250'); Perf (Canyon) 9932-52' w/1 SPF; Acid (9932-
52') 30,000 gals; Flwd 290,000 CFGPD (9932-52'); TD 11,339', SI.