

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

C/SF

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other
- 
2. NAME OF OPERATOR  
Yates Petroleum Corporation
- 
3. ADDRESS OF OPERATOR  
207 South 4th St., Artesia, NM 88210
- 
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1980 FNL & 660 FEL, Sec. 17-20S-29E  
AT SURFACE:  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:
- 
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

- |                      |                                     |
|----------------------|-------------------------------------|
| TEST WATER SHUT-OFF  | <input type="checkbox"/>            |
| FRACTURE TREAT       | <input checked="" type="checkbox"/> |
| SHOOT OR ACIDIZE     | <input checked="" type="checkbox"/> |
| REPAIR WELL          | <input type="checkbox"/>            |
| PULL OR ALTER CASING | <input type="checkbox"/>            |
| MULTIPLE COMPLETE    | <input type="checkbox"/>            |
| CHANGE ZONES         | <input type="checkbox"/>            |
| ABANDON*             | <input type="checkbox"/>            |
| (other)              | <input type="checkbox"/>            |

- □ □ □ □ □ □

RECEIVED  
JAN 18 1982 (NOTE: Repro chan)

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

U.S. GEOLOGICAL SURVEY  
KOSOVILLE, KENT, OHIO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

This well has depleted to point where well will not sustain flow from perforations 11823-867'. We propose to set a standing valve in packer at 11805', pull tubing, additionally perforate the Morrow selectively from 11511-668', run tubing, packer & RBP and stimulate new perforations, pull RBP and produce all Morrow perforations thru tubing and packer at about 11470'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Eddie L. Lutz TITLE Engineer DATE 1-15-82

~~APPROVED~~

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER V. CHESTER  
CONDITIONS OF APPROVAL, IF ANY:

DATE \_\_\_\_\_

JAN 18 1982

FOR

JAMES A. GILLHAM

DISTRICT SUPERVISOR \*See Instructions on Reverse Side