

Application for Permit to Drill Tracy "D" No. 1

Page No. 2

September 12, 1975

Projected T.D. is 11,600'. Primary objective is the Morrow Sand, secondary objectives are Wolfcamp, Canyon, Strawn and Atoka.

Mr. Francis Tracy, Jr., 1601 N. Guadalupe Street, Carlsbad, New Mexico, telephone No. 505/885-4857, owns the land under our location and access road. Mr. Tracy has been notified of our intent to drill.

If it is a dry hole, the well will be plugged in accordance with New Mexico Oil Conservation Commission requirements.

The proposed casing program consists of:

13-3/8" casing set at 400' with cement circulated to surface.

9-5/8" casing set at 3000' with cement circulated to surface.

5-1/2" casing set at T.D. 11,600' and cemented with sufficient volume to fill the annular space from T.D. to 8000'.

In addition to the blowout preventer equipment shown on the attached plat, the following equipment will be in use before drilling out from under the 9-5/8" intermediate casing:

1. Swaco adjustable choke.
2. Pit volume totalizer.
3. Flow line sensor.
4. Degasser.

Also, prior to drilling out under the 9-5/8", the BOP's and related control equipment will be pressure tested to rated working pressure by Yellow Jacket Tools and Services, Inc.

Please contact me at the above address if further information is needed to properly evaluate this request.

Yours very truly,



E. Y. Wilder
Region Operations Manager
Southwest Region
E & P Division

EYW/lis

Attachments