

RECEIVED NEW MEXICO OIL CONSERVATION COMMISSION

OCT 23 1975

O. C. C.
ARTESIA, OFFICE

Form G-103
Supersedes G-11
G-103 and G-103
Effective 10-61

5a. Indicate type of permit	Permit <input checked="" type="checkbox"/> XX Fee <input type="checkbox"/>
5b. Permit No. (G-103, G-103, G-103)	L-3356

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT..." (FORM G-101) FOR SUCH PROPOSALS.)

1. Well <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-	7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation ✓	8. Name of Lessee Little Indian Basin St. ES Com
3. Address of Operator 207 South 4th Street - Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER <u>0</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>21S</u> RANGE <u>22E</u> NMPM.	10. Field, Pool, or Well Unit Wildcat-Morrow
15. Elevation (Show whether DF, RT, GR, etc.) 4068' GR	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated work) SEE RULE 1103.

TD 2100' - Ran 47 joints of 8-5/8" 32# K-55 new casing (2098') set at 2098', 1-Guide Shoe, insert collar, 3 centralizers and 2 baskets at 700 & 610'. Cemented w/650 sacks of Hali-lite w/5% Gilsonite, 0.5% floccle 2% CaCl followed by 150 sacks Class C 2% CaCl. PD 5:05 AM 10-20-75. Cement circulated. WOC 18 hours, nipples up and installed BOP's and tested to 1000#. OK. Drilled cement and tested shoe to 600#. OK. Reduced hole to 7-7/8" and resumed drilling

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Christine Tomlinson TITLE Geol Secty

10-22-75

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II

OCT 24 1975

CONDITIONS OF APPROVAL, IF ANY: