

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other Depleted Gas Well

2. NAME OF OPERATOR
Penroc Oil Corporation

3. ADDRESS OF OPERATOR
P. O. Drawer 831, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' ENL, 1980' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

☐
☐
☐
☐
☒
☐
☐
☒

5. LEASE
NM-0557562

RECEIVED

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

JUL 13 1982

7. UNIT AGREEMENT NAME

O. C. D.

8. FARM OR LEASE NAME
Wright Federal

ARTESIA, OFFICE

9. WELL NO.
2

10. FIELD OR WILDCAT NAME

Angell Ranch Atoka-Morr. (Gas)

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
6-20S-28E

12. COUNTY OR PARISH
Eddy

13. STATE
New Mexico

14. API NO.
30-015-21635

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3364.5 GR 3380.5' KDB

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

(Refer to 9-331 dated 1-1-82)

1. 3-09-82 Set CIBP @ 9300' and dump bailer 50' cement on top.
2. 3-10-82 Cut off 4 1/2", 11.60#, N-80 casing @ 7192'. Pull casing.
3. 3-12-82 Set 150' cement plug 7260'-7110' in and out of 4 1/2" csg. stub.
4. 3-13-82 Set 100' cement plug 4302'-4202' across top Bone Spring.
5. " Set 100' cement plug 2550'-2450' (50' in and out of 8 5/8" casing set @ 2500').
6. " Set 15 sack cement plug in top 8 5/8" csg w/dry hole marker in place.

Will advise when surface stipulations have been met for final inspection and approval.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED B. J. Dancy TITLE President DATE 3-23-82

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side