

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)Form approved: *7/2/5*
Budget Bureau No. *22-R1424*

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		RECEIVED		5. LEASE DESIGNATION AND SERIAL NO. NM 17100	
2. NAME OF OPERATOR Yates Petroleum Corporation		OCT 15 1975		8. FARM OR LEASE NAME Stonewall "DS" Federal	
3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, NM 88210		ARTESIA, OFFICE		9. WELL NO. 2	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1980' FSL & 1980' FEL of Sec. 29-20S-28E				10. FIELD AND POOL, OR WILDCAT No. Burton Flats	
				11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29-20S-28E Unit J NMPM	
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3229' GR		12. COUNTY OR PARISH Eddy	
				13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐FRACTURE TREAT ☐SHOOT OR ACIDIZE ☐REPAIR WELL ☐(Other) ☐PULL OR ALTER CASING ☐MULTIPLE COMPLETE ☐ABANDON* ☐CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒FRACTURE TREATMENT ☐SHOOTING OR ACIDIZING ☐(Other) ☐REPAIRING WELL ☐ALTERING CASING ☐ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-25-75 - Spudded 17½" hole at 11:00 PM 9-25-75.

TD 556' - Ran 19 joints of 13-3/8" 48# casing (576') set at 556' KB. Cemented w/550 sacks of Class "C" 4% CaCl. Cement circulated. PD 4:00 PM 9-27-75. WOC 12 hours, cut off landing joint, nipped up flow nipple, drilled plug and reduced hole to 12¼" and resumed drilling.

TD 2800' - Ran 70 jts of 8-5/8" 24&32# casing (2829') set at 2820' K B. Cmt'd w/950 sx Hali-lite + 200 sx of Class C 2% CaCl. Cmt did not circ. PD 2:45 AM 10-3-75. WOC 8 hrs. Ran Temp. Survey, found top of cmt at 1250'. Dumped 1½ yards of pea gravel and ran 1" tbg to 966', spotted 50 sx Class C 4% CaCl. WOC 3 hrs and ran 1", found top of cmt at 735'. Spotted 325 sx Class C 4% CaCl. Cement circulated. PD 9:00 PM 10-3-75. WOC 18 hours. Nipped up, installed BOP's and tested to 1600#. OK. Drilled plug and tested shoe to 600#. OK. Reduced hole to 7-7/8" and resumed drilling.

RECEIVED

OCT 10 1975

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Engineer

DATE 10-10-75

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

OCT 14 1975
T. L. BEEKHUIS
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side