

IP (Atoka) Perfs 10,546-556' F 13,230 MCFGPD + 140 B Cond.
Pot based on 1 hr test thru 48/64" chk. GOR 94,500; Grav (Cond)
54.8; TP 940#

12-3-9 NM

EDDY
YATES PETROLEUM CORP.

Wildcat
2 Stonewall "DS" Federal
Sec 29, T20S, R28E Page #2

NM

11-6-75 Drlg 10,943'; "Tight"
11-12-75 TD 11,530'; Rng Logs "Tight"
11-19-75 TD 11,530'; "Tight"
DST (Wolfcamp) 9525-70', open 2 hrs 45 mins,
GIS in 12 mins, rec 912' Cond + 150' FW +
540' DM, 1 hr 30 min ISIP 4490#, FF 231-577#,
5 hr FSIP 3852#, HP 4900-4900#, BHT 150 deg
12-8-75 TD 11,530'; PBD 11,370'; Complete (Hold for
Info)
Perf (Morrow) 11,408-418' w/4 SPF
Acid (11,408-418') 500 gals
Hole Full wtr (11,408-418')
PB to 11,370'

12-3-9 NM

12-8-75 Continued
Perf (Atoka) 10,546-556' w/4 SPF
Natural (10,546-556')
12-15-75 TD 11,530'; PBD 11,370'; Complete
Atoka Discovery in Burton Flat (Morrow)
Field
LOG TOPS: Yates 581', Delaware 2830', Bone
Spring 4870', Wolfcamp 8738', Strawn 10,195',
Atoka 10,418', Morrow 11,019', Lower Morrow
11,335'
12-20-75 COMPLETION ISSUED

12-3-9 NM
IG 30 015 70039 73