

2-18-76

NRM PET. CORP.
1 Golden Federal
API 30-015-21649

GOLDEN LANE (MRRW): (9-8-75); 14,000' RT; Sec 33-20s-30e; 910' FNL, 660' FWL D
Sec: 6 mi N & 14 mi E/Carlsbad; Elev. 3353' GL; Spud 9-25-75; 20" 450'/750 sx; 13-3/8"
1615'; 8-5/8" 4040'/1575 sx; DST 11,090-138', op 5 hrs 30 mins, GTS in 5 mins @ est
500,000-1,000,000 CFGPD, rec 9200' wtr, 1 hr ISIP 5251#, FP 1570-2030#, 13 hr FSIP
5282#, HP 5778-5778#, BHT 170 degs; DST 11,162-232', op 4 hrs 20 mins, (1500' WB) rec WB + 110' GCM + 15 gals cond,
1 hr ISIP 5042#, FP 655-699#, 8 hr FSIP 5130#, HP 5880-5880#, BHT 170 degs; 5-1/2" 12,642'; Perf (Morrow) 12,413-
419'; Perf (Strawn) 11,175-179', 11,183', 11,194', 11,192', 11,195-198', 11,207-209', 11,221', 11,222', 11,224', 11,
225'; BP @ 11,400'; Acid (11,175-225') 5000 gals; BP @ 11,150'; Perf @ 11,117', 11,118', 11,121', 11,122', 11,123',
11,124', 11,125', 11,126', 11,127', 11,130', 11,131', 11,132', 11,133' w/1 SPI; Acid (11,117-133') 3000 gals; Flwd
2,200,000 CFGPD/24 hrs thru 22/64" chk (11,117-133'); Flwd 1,000,000 CFGPD + 20 BW/7 hrs, 24/64" chk, TP 750#
(11,117-133'); Log Tops: Yates 1425', Delaware Sand 4050', Brushy Canyon 4975', Bone Spring 6620', Third Bone Spring
Sand 9565', Wolfcamp lime 9958', Cisco-Canyon 10,698', Strawn 11,080', Atoka 11,305', Morrow lime 11,617', Morrow
Sand 12,110'; TD 12,642', PBD 11,150', Tstg.