

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

RECEIVED

FEB 4 1976

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. E-5230

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Perry R. Bass 3. Address of Operator P. O. Box 2760 Midland, TX 79701 4. Location of Well UNIT LETTER <u>H</u> <u>1880</u> FEET FROM THE <u>N</u> LINE AND <u>790</u> FEET FROM THE <u>E</u> LINE, SECTION <u>16</u> TOWNSHIP <u>21-S</u> RANGE <u>30-E</u> NMPM.	7. Unit Agreement Name Big Eddy Unit 8. Farm or Lease Name Big Eddy Unit 9. Well No. 45 10. Field and Pool, or Wildcat Wildcat 12. County Eddy
15. Elevator. (Show whether DF, RT, GR, etc.) 3306' Gr, Graded 3303', KB 3315'	

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-18-76: With DP at 1023' ran 300 sks Class C cement. Estimated top of plug at 510' WOC 5½ hrs. Tagged mushy cement at 775'. Pulled out of hole with plugged drill pipe (372'). WOC additional 5 hrs - went in hole to base of surface casing (468') - circulated with partial returns - recovered wet cement. Spotted 50 sks Class C cement with bottom at 464' - top of plug should be at 364'. WOC 5 hrs - tagged solid cement at 454'. Spotted additional 50 sks from 454' to 350'. Surface plug and marker not yet installed.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. P. Foster W. P. Foster TITLE Senior Petroleum Engineer DATE February 3, 1976.

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: