

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

FEB 4 1976

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-5230	
7. Unit Agreement Name	
Big Eddy Unit	
8. Farm or Lease Name	
Big Eddy Unit	
9. Well No.	
45	
10. Field and Pool, or Wildcat	
Wildcat	
12. County	
Eddy	

SUNDY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	2. Name of Operator	3. Address of Operator	4. Location of Well
	Perry R. Bass	P. O. Box 2760 Midland, TX 79701	UNIT LETTER H, 1880 FEET FROM THE N LINE AND 790 FEET FROM THE E LINE, SECTION 16 TOWNSHIP 21-S RANGE 30-E NMPM.
15. Elevation (Show whether DF, RT, GR, etc.)			
3306' Gr, Graded 3303', KB 3315'			

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☒
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-18-76: With DP at 1023' ran 300 sks Class C cement. Estimated top of plug at 510' WOC 5½ hrs. Tagged mushy cement at 775'. Pulled out of hole with plugged drill pipe (372'). WOC additional 5 hrs - went in hole to base of surface casing (468') - circulated with partial returns - recovered wet cement. Spotted 50 sks Class C cement with bottom at 464' - top of plug should be at 364'. WOC 5 hrs - tagged solid cement at 454'. Spotted additional 50 sks from 454' to 350'. Surface plug and marker not yet installed.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. P. Foster W. P. Foster TITLE Senior Petroleum Engineer DATE February 3, 1976.

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: