NO. OF COPIES RECEIVED				**		115 21685	
DISTRIBUTION	w	.W MEXICO OIL CONSERVATION COMMISSIO.				15-21685	
SANTA FE ,	<del></del>				Revised 1-1-6	55	
FILE	F-	R	ECEIVE	D		Type of Lease	
U.S.G.S.	· ·				STATE		
LAND OFFICE		•	NOV 20 1975			& Gas Lease No.	
OPERATOR			1404 ~ 0 1010		E	-5230	
APPLICATION	N FOR BEDUIT TO	DOUL DEEDEN (	NO DE LETA				
APPLICATION	N PUR PERMIT TO	DRILL, DEEPEN, (	ARTESIA, OFFICE		7. Unit Agre	ement Name	
			•		Rig	Eddy Unit	
b. Type of Well DRILL X		DEEPEN	PLUG	BACK	8. Form or L	ease Name	
OIL GAS WELL	OTHER		SINGLE MU	ZONE	Big	Eddy anit	
2. Name of Operator					9. Well No.		
Perry R. Bass /						#45	
3. Address of Operator					10. Field and Pool, or Wildcat		
P. O. Box 2760	Midland, To				KLLLLLL MITG	cat Velaure	
UNIT LETTE	R LOO	:ATEB 1880 F	EET FROM THE <u>NOTE</u>	1 LINE			
AND 790° FEET FROM	THE East LIV	E OF SEC. 16 TO	vp. 21-S RGE. 30	)-E NMPM			
					12. County		
				7777777	Eddy		
			9. Proposed Depth	19A. Formatio	7777777	20. Rotary or C.T.	
			5000'	Delaws	i	Rotary	
21. Elevations (Show whether DF,		& Status Plug. Bond 2		D. C.		. Date Work will start	
3306' GR	Blan	tect			Janua	ry, 1976	
23.	F	PROPOSED CASING AND	CEMENT PROGRAM				
SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	SACKS OF	F CEMENT	EST. TOP	
122	8.625	24	450	300 sx			
7 7/8	5½	14	5000	300 sx			
				•			
•	•	•	•	•	•	'	
Drilling Procedure, BOPE diagram, anticipated formation tops and Surface Use Plan attached.							
						,	
•							
						VAL VALID PAYS UNLESS	
				,		COMMENCED,	
				E1/18		24-76	
				EXP	IKES		
	OPOSED PROGRAM: IF	PROPOSAL IS TO DEEPEN OF	I PLUG BACK, GIVE DATA (	ON PRESENT PR	ODUCTIVE ZONE	AND PROPOSED NEW PRODUC	
hereby centify that the information	n above is true and com	plete to the best of my kn	owledge and belief.				
II, D. Ja	to.						
Signed UV. 7 700		Tule Sr. Petrol	.eum Engineer		Date 11.	-17 <b>-</b> 75	
APPROVED BY W. A. State Use)  SUPERVISOR, DISTRICT II  DATE NOV 2 4 1975							
APPROVED BY WU, U1, S	ANY:	_ TITLE	, Dimer H		DATE NUV	2 1 101 0	

Cement must be circulated to surface behind 8 1/8 +5 1/2 casing