NO. UN COPIES RECEIVED	3	•	and the	Form C-103
DISTR:BUTION				Supersedes Old
SANTA FE		NEW MEXICO OIL CONS	ERVATION COMMISSION	C-102 and C-103 ` Effective 1-1-65
FILE	11			
U.S.G.S.			RECEIVED	5a. Indicate Type of Lease
I AND FICE			KEGEIVED	State Fee X
LAND FICE				100 45
OPER OR			MAD 9 & 107C	5, State Oil & Gas Lease No.
MAR 2 6 1976				
/OA NAT HEE THIS PA	SUNDRY	NOTICES AND REPORTS ON	WELLS	
USE	**APPLICATION	FOR PERMIT - " (FORM C-101) FOR SUC	ACK TO A DIFFERENT RESERVOIR.	
GAS	-		ARTESIA, OFFICE	7. Unit Agreement Name
CAS WELL X OTHER-				
•				8. Farm or Lease Name
Cities Service Oil Company /				C.D.M. A Com.
				9. Well No.
Box 1919 - Midland, Texas 79701				1
4. Location of Well				10. Field and Pool, or Wildcat
UNIT LETTERD		O FEET FROM THE North	LINE AND FEET FROM	Undesignated Morrow
THE West Line, Section 29 TOWNSHIP 21S RANGE 27E NMPM.				
THE West	INE, SECTION	29 TOWNSHIP 21S	RANGE 27E	Allillillilli
······································	mm		DE DE CD	
		15. Elevation (Show whether 3141 GR	Dr, RI, Gr., etc.)	12. County
<u> </u>			······	Eddy
Check Appropriate Box To Indicate Nature of Notice, Report or Other Data				
NOTIO	CE OF INT	ENTION TO:	SUBSEQUEN	T REPORT OF:
_	_			·
PERFORM REMEDIAL WORK		PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON]		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING]	CHANGE PLANS	CASING TEST AND CEMENT JOB	
			OTHER Well completion	data x
OTHER				
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date is any proposed work) SEE RULE 1903.				
work) SEE RULE 1103.	mpleted Oper	dions (Clearly state all pertment deta	, - ·· g · · · · , · · · · · · · · · · · · · · · · · · ·	estimated date
work) SEE RULE 1103.				
work) SEE RULE 103. T.D. 11690! Shal	le & Lime	PBTD 11651'. Shut-i	n waiting on pipeline c	onnection.
T.D. 11690' Shall Drilled and clea	le & Lime ned out	PBTD 11651'. Shut-i	n waiting on pipeline c ed hole w/258 bbls fres	onnection. h water w/2% KCl and then
T.D. 11690' Shall Drilled and clear spotted 100 gals	le & Lime ned out 10% Ace	e PBTD 11651'. Shut-i to 11651' and circulate tic acid @ 11470 - 113'	n waiting on pipeline c ed hole w/258 bbls fres 70. Pressured casing	onnection. h water w/2% KCl and then to 1500# - Held O.K. Perf-
T.D. 11690' Shall Drilled and clea spotted 100 gals orated the Morro	le & Lime ned out 10% Ace w zone w	e PBTD 11651'. Shut-i to 11651' and circulate tic acid @ 11470 - 113 1/2-0.41" holes each @ 1	n waiting on pipeline ced hole w/258 bbls fresh70. Pressured casing 11387, 11389,	onnection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394',
T.D. 11690' Shall Drilled and clea spotted 100 gals orated the Morro 11396', 11398',	le & Lime ned out 10% Ace w zone w 11400',	e PBTD 11651'. Shut-i to 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 1 11402', 11404', 11406'	n waiting on pipeline ced hole w/258 bbls fresh70'. Pressured casing 11387', 11388', 11389', 11409', 11414', 11414	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437',
T.D. 11690' Shall Drilled and clea spotted 100 gals orated the Morro 11396', 11442' a	le & Lime ned out 10% Ace w zone w 11400', nd 11445	e PBTD 11651'. Shut-i to 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 1 11402', 11404', 11406' '. Ran and set 2-7/8"	n waiting on pipeline ced hole w/258 bbls fresh 70'. Pressured casing the shift of	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'.
mork) SEE RULE 1703. T.D. 11690' Shal Drilled and clea spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' a 12 hr SITP 40#.	le & Limened out 10% Ace w zone w 111,00', nd 111115	e PBTD 11651'. Shut-ito 11651' and circulate tic acid @ 11470 - 1137/2-0.41" holes each @ 11402', 11406'. Ran and set 2-7/8" part of load and swab	n waiting on pipeline could hole w/258 bbls fresh 70'. Pressured casing of the could be could	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445'
mork) SEE RULE 1703. T.D. 11690' Shall Drilled and clea spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' a 12 hr SITP 40#. w/5000 gals 7-1/	le & Lime ned out 10% Ace w zone w 11400', nd 11445 Swabbed 2% HCl a	e PBTD 11651'. Shut-ito 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11406' ('. Ran and set 2-7/8" part of load and swab cid w/additives + 1000	n waiting on pipeline of the dolor of the do	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press.
mork) SEE RULE 1703. T.D. 11690' Shall Drilled and clea spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' a 12 hr SITP 40#. w/5000 gals 7-1/7500#, formation	le & Limened out 10% Ace w zone w 11400', nd 11445 Swabbed 2% HCl a broke @	e PBTD 11651'. Shut-ito 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11406' i. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 2 7500#, min. press. 50	n waiting on pipeline of the hole w/258 bbls fresh 70'. Pressured casing 11387', 11388', 11389', 11409', 11411', 11414 OD tubing and a Baker 10ed dry. Acidized thru SCF Nitrogen/bbl. + 60 00#, AIR 8.3 B/M (5.2 ac	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP
T.D. 11690' Shall Drilled and clea spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' a 12 hr SITP 40#. w/5000 gals 7-1/7500#, formation 4200#, 10 min SI	le & Lime ned out 10% Ace w zone w 11400', nd 11445 Swabbed 2% HCl a broke @ P 3600#.	e PBTD 11651'. Shut-ito 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11406' i. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 7500#, min. press. 50 12 hr. SITP 3700#.	n waiting on pipeline ced hole w/258 bbls fresh 70'. Pressured casing 11387', 11388', 11389', 11409', 11411', 11414 OD tubing and a Baker 10ed dry. Acidized thru SCF Nitrogen/bbl. + 60 00#, AIR 8.3 B/M (5.2 ac 710wed 10 BLW + gas © reset to the result of the second se	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs
T.D. 11690' Shall Drilled and clea spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' a 12 hr SITP 40#. w/5000 gals 7-1/7500#, formation 4200#, 10 min SI thru 1" choke, F	le & Lime ned out 10% Ace w zone w 11400', nd 11445 Swabbed 2% HC1 a broke @ P 3600#.	e PBTD 11651'. Shut-it to 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11406', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 7500#, min. press. 50 12 hr. SITP 3700#. Loaded tubing w/63 bb	n waiting on pipeline of the doctor of the w/258 bbls fresh 70'. Pressured casing 11387', 11388', 11389', 11409', 11411', 11414 OD tubing and a Baker 100d dry. Acidized thru SCF Nitrogen/bbl. + 60 CO#, AIR 8.3 B/M (5.2 ac Flowed 10 BLW + gas © rels of fresh water w/2% 1	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11442' at 12 hr SITP 40#. w/5000 gals 7-1/7500#, formation 4200#, 10 min SI thru 1" choke, Fulled tubing an	le & Limened out 10% Ace w zone w 111,00', nd 111115 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer	e PBTD 11651'. Shut-it to 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11404', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 27500#, min. press. 500 12 hr. SITP 3700#. Loaded tubing w/63 bb set @ 11297'. Perfor	n waiting on pipeline of the doctor of the w/258 bbls fresh 70'. Pressured casing 11387', 11388', 11389', 11409', 11411', 11414 OD tubing and a Baker 10ed dry. Acidized thru SCF Nitrogen/bbl. + 60 00#, AIR 8.3 B/M (5.2 ac 110 bbl.) at a 12 control of the water w/2% 12 at a 12 control of the water w/2% 12 at a 12 control of the water w/2% 12 at a 12 control of the water w/2% 12 at a 12 control of the water w/2% 12 at a 12 control of the water w/2% 12 at a 12 control of the water w/2% 12 at a 12 control of the water w/2% 12 control of	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' at 12 hr SITP 40#. w/5000 gals 7-1/7500#, formation 4200#, 10 min SI thru 1" choke, Fulled tubing an at 11320', 11321'	le & Limened out 10% Ace w zone w 111,00', nd 111115 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer	PBTD 11651'. Shut-ito 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 7500#, min. press. 500 12 hr. SITP 3700#. Itoaded tubing w/63 bb. set @ 11297'. Perfor 11324', 11326', 1132	n waiting on pipeline could hole w/258 bbls fresh 70'. Pressured casing 11387', 11388', 11389', 11409', 11411', 11414 OD tubing and a Baker 10ed dry. Acidized thru SCF Nitrogen/bbl. + 6000#, AIR 8.3 B/M (5.2 ac 11304', 11329', 11330', 113	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and
T.D. 11690' Shall Drilled and clea spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' a 12 hr SITP 40#. w/5000 gals 7-1/7500#, formation 4200#, 10 min SI thru 1" choke, F pulled tubing an @ 11320', 11321' 11338'. Ran and	le & Limened out 10% Ace w zone w 11400', nd 11445 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer , 11322' l set a H	PBTD 11651'. Shut-it to 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11404', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 7500#, min. press. 50 12 hr. SITP 3700#. Loaded tubing w/63 bb: set @ 11297'. Perfor 1, 11324', 11326', 11328 aker Model DB packer w	n waiting on pipeline of the doctor of the w/258 bels fresh 70'. Pressured casing 11387', 11388', 11389', 11409', 11411', 11414' OD tubing and a Baker 100 doy. Acidized thru SCF Nitrogen/bbl. + 60 DO#, AIR 8.3 B/M (5.2 ac Flowed 10 BLW + gas © related the Upper Morrow z 8', 11329', 11330', 113 ith a Baker Type "F" pressure of the pressure of the same o	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'.
T.D. 11690' Shall Drilled and clea spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' a 12 hr SITP 40#. w/5000 gals 7-1/7500#, formation 4200#, 10 min SI thru 1" choke, F pulled tubing an 2 11320', 11321' 11338'. Ran and Ran 2-7/8" OD tu	le & Lime ned out 10% Ace w zone w 11400', nd 11445 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer 11322' i set a Eabing and	to 11651'. Shut-ito 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 /2500#, min. press. 50 /12 hr. SITP 3700#. I Loaded tubing w/63 bb set @ 11297'. Perfor 1, 11324', 11326', 11328 aker Model DB packer will set seal assembly in	n waiting on pipeline of the doctor of the w/258 bbls fresh 70'. Pressured casing 11387', 11388', 11389', 11409', 11411', 11414 OD tubing and a Baker 1004 dry. Acidized thru SCF Nitrogen/bbl. + 60 CO#, AIR 8.3 B/M (5.2 ac 11000 fresh water w/2% lated the Upper Morrow z ated the Upper Morrow z	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'. 1370' with a Baker Lok-set
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' a 12 hr SITP 40#. w/5000 gals 7-1/7500#, formation 4200#, 10 min SI thru 1" choke, Fulled tubing an 21320', 11321' 11338'. Ran and Ran 2-7/8" OD two packer set @ 112	le & Lime ned out 10% Ace w zone w 11400', nd 11445 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer 11322' set a Eubing and 203'. 1	to 11651'. Shut-it to 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 f 7500#, min. press. 50 f 12 hr. SITP 3700#. Loaded tubing w/63 bb set @ 11297'. Perfor f, 11324', 11326', 11328 aker Model DB packer will set seal assembly in 2 hr. SITP 3000#. Flow	n waiting on pipeline of the dole w/258 bbls fresh 70'. Pressured casing 11387', 11388', 11389', 11409', 11411', 11414 OD tubing and a Baker 1006 dry. Acidized thru SCF Nitrogen/bbl. + 60 CO#, AIR 8.3 B/M (5.2 ac Flowed 10 BLW + gas © related the Upper Morrow z 8', 11329', 11330', 113 ith a Baker Type "F" pred the Baker Ba	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'. 1370' with a Baker Lok-set 2 rate of 299 MCFD thru 1"
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' a 12 hr SITP 40#. w/5000 gals 7-1/7500#, formation 4200#, 10 min SI thru 1" choke, Froulled tubing an e 11320', 11321' 11338'. Ran and Ran 2-7/8" OD tupacker set e 112 choke. FTP 10#.	le & Limened out 10% Ace w zone w 11400', nd 11445 Swabbed 2% HC1 a broke @ P 3600#. TP 15#. d packer , 11322' l set a E abing and 203'. 1	to 11651'. Shut-it to 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11406', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 27500#, min. press. 500 12 hr. SITP 3700#. I Loaded tubing w/63 bb set @ 11297'. Perfor 1, 11324', 11326', 1132 Baker Model DB packer will set seal assembly in 2 hr. SITP 3000#. Flowed thru Upper Morrow per set with the set will be set seal assembly in 2 hr. SITP 3000#. Flowed thru Upper Morrow per set will be set will	n waiting on pipeline of the dole w/258 bbls fresh 70'. Pressured casing 11387', 11388', 11389', 11409', 11411', 11414 OD tubing and a Baker 100d dry. Acidized thru SCF Nitrogen/bbl. + 60 00#, AIR 8.3 B/M (5.2 ac Flowed 10 BLW + gas © related the Upper Morrow z 8', 11329', 11330', 113 ith a Baker Type "F" pressured 41 BLW/7 hrs + gas © 10 refs 11320 - 11338' w/50	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'. 1370' with a Baker Lok-set @ rate of 299 MCFD thru 1" 000 gals 7-1/2% HCl acid
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' at 12 hr SITP 40%. w/5000 gals 7-1/7500%, formation 4200%, 10 min SI thru 1" choke, Froulled tubing an and 11320', 11321' 11338'. Ran and Ran 2-7/8" OD tupacker set @ 112 choke, FTP 10%. + 1000 SCF Nitro	le & Lime ned out 10% Ace w zone w 111,00', nd 111,15 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer 11322' i set a E bing and 203'. I Acidize ogen/bbl	to 11651'. Shut-it to 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 12 hr. SITP 3700#. Loaded tubing w/63 bb set @ 11297'. Perfor 11324', 11326', 11328 aker Model DB packer will set seal assembly in 2 hr. SITP 3000#. Flowed thru Upper Morrow per Max. press. 6100#, m	n waiting on pipeline of the dole w/258 bbls fresh 70'. Pressured casing 11387', 11388', 11389', 11409', 11411', 11414 OD tubing and a Baker 10ed dry. Acidized thru SCF Nitrogen/bbl. + 60 DO#, AIR 8.3 B/M (5.2 ac 110000 fresh water w/2% lated the Upper Morrow z 8', 11329', 11330', 113 ith a Baker Type "F" pressed 41 BLW/7 hrs + gas 6 arfs 11320 - 11338' w/50 min. press. 5550#, Average	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'. 1370' with a Baker Lok-set 2 rate of 299 MCFD thru 1" 000 gals 7-1/2% HCl acid age treating press. 5800#,
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' at 12 hr SITP 40%. w/5000 gals 7-1/7500%, formation 4200%, 10 min SI thru 1" choke, Froulled tubing an and 11320', 11321' 11338'. Ran and Ran 2-7/8" OD tupacker set @ 112 choke, FTP 10%. + 1000 SCF Nitro AIR 10.1 B/M (6	le & Lime ned out 10% Ace w zone w 111,00', nd 111115 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer 11322' l set a E bing and 203'. I' Acidizogen/bbl. l acid	to 11651'. Shut-it to 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11404', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 27500#, min. press. 500 12 hr. SITP 3700#. It Loaded tubing w/63 bb set @ 11297'. Perfor 1, 11324', 11326', 1132 Baker Model DB packer will set seal assembly in 2 hr. SITP 3000#. Flowed thru Upper Morrow per Max. press. 6100#, respectively.	n waiting on pipeline of the dock of hole w/258 bbls fresh 70. Pressured casing 11387, 11388, 11389, 11387, 11409, 11411, 11414, OD tubing and a Baker 1 bed dry. Acidized thru SCF Nitrogen/bbl. + 60 00#, AIR 8.3 B/M (5.2 ac 1 lowed 10 BLW + gas © related the Upper Morrow z 8, 11329, 11330, 113 ith a Baker Type "F" pressed 41 BLW/7 hrs + gas © 1 lowed 41 lowed	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'. 1370' with a Baker Lok-set @ rate of 299 MCFD thru 1" 000 gals 7-1/2% HCl acid
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' at 12 hr SITP 40%. w/5000 gals 7-1/7500%, formation 4200%, 10 min SI thru 1" choke, Froulled tubing an and 11320', 11321' 11338'. Ran and Ran 2-7/8" OD tupacker set @ 112 choke, FTP 10%. + 1000 SCF Nitro AIR 10.1 B/M (6	le & Lime ned out 10% Ace w zone w 111,00', nd 111115 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer 11322' l set a E bing and 203'. I' Acidizogen/bbl. l acid	to 11651'. Shut-it to 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 12 hr. SITP 3700#. Loaded tubing w/63 bb set @ 11297'. Perfor 11324', 11326', 11328 aker Model DB packer will set seal assembly in 2 hr. SITP 3000#. Flowed thru Upper Morrow per Max. press. 6100#, m	n waiting on pipeline of the dock of hole w/258 bbls fresh 70. Pressured casing 11387, 11388, 11389, 11387, 11409, 11411, 11414, OD tubing and a Baker 1 bed dry. Acidized thru SCF Nitrogen/bbl. + 60 00#, AIR 8.3 B/M (5.2 ac 1 lowed 10 BLW + gas © related the Upper Morrow z 8, 11329, 11330, 113 ith a Baker Type "F" pressed 41 BLW/7 hrs + gas © 1 lowed 41 lowed	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'. 1370' with a Baker Lok-set 2 rate of 299 MCFD thru 1" 000 gals 7-1/2% HCl acid age treating press. 5800#,
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' at 12 hr SITP 40%. w/5000 gals 7-1/7500%, formation 4200%, 10 min SI thru 1" choke, Froulled tubing an and 11320', 11321' 11338'. Ran and Ran 2-7/8" OD tupacker set @ 112 choke, FTP 10%. + 1000 SCF Nitro AIR 10.1 B/M (6	le & Lime ned out 10% Ace w zone w 111,00', nd 111115 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer 11322' l set a E bing and 203'. I' Acidizogen/bbl. l acid	to 11651'. Shut-it to 11651' and circulate tic acid @ 11470 - 113' /2-0.41" holes each @ 11402', 11404', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 27500#, min. press. 500 12 hr. SITP 3700#. It Loaded tubing w/63 bb set @ 11297'. Perfor 1, 11324', 11326', 1132 Baker Model DB packer will set seal assembly in 2 hr. SITP 3000#. Flowed thru Upper Morrow per Max. press. 6100#, respectively.	n waiting on pipeline of the dock of hole w/258 bbls fresh 70. Pressured casing 11387, 11388, 11389, 11387, 11409, 11411, 11414, OD tubing and a Baker 1 bed dry. Acidized thru SCF Nitrogen/bbl. + 60 00#, AIR 8.3 B/M (5.2 ac 1 lowed 10 BLW + gas © related the Upper Morrow z 8, 11329, 11330, 113 ith a Baker Type "F" pressed 41 BLW/7 hrs + gas © 1 lowed 41 lowed	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'. 1370' with a Baker Lok-set 7 rate of 299 MCFD thru 1" 1000 gals 7-1/2% HCl acid age treating press. 5800#, 10 min SIP 2800#, 15 min
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' at 12 hr SITP 40%. w/5000 gals 7-1/7500%, formation 4200%, 10 min SI thru 1" choke, Froulled tubing an and 11320', 11321' 11338'. Ran and Ran 2-7/8" OD tupacker set @ 112 choke, FTP 10%. + 1000 SCF Nitro AIR 10.1 B/M (6	le & Lime ned out 10% Ace w zone w 111,00', nd 111115 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer 11322' l set a E bing and 203'. I' Acidizogen/bbl. l acid	to 11651'. Shut-it to 11651' and circulate tic acid @ 11170 - 113' /2-0.41" holes each @ 111402', 11401', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 12 hr. SITP 3700#. Loaded tubing w/63 bb. set @ 11297'. Perfor 1, 11324', 11326', 11328 aker Model DB packer will set seal assembly in 2 hr. SITP 3000#. Flowed thru Upper Morrow performance of the best of the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the loc	n waiting on pipeline of the doctor of the waiting on pipeline of the doctor of the waiting on pipeline of the waiting of the waiting of the waiting and a Baker of the waiting and a Baker of the waiting and a Baker of the waiting o	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'. 1370' with a Baker Lok-set 7 rate of 299 MCFD thru 1" 1000 gals 7-1/2% HCl acid age treating press. 5800#, 10 min SIP 2800#, 15 min
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' at 12 hr SITP 40%. w/5000 gals 7-1/7500%, formation 4200%, 10 min SI thru 1" choke, Froulled tubing an and 11320', 11321' 11338'. Ran and Ran 2-7/8" OD tupacker set @ 112 choke, FTP 10%. + 1000 SCF Nitro AIR 10.1 B/M (6	le & Lime ned out 10% Ace w zone w 111,00', nd 111115 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer 11322' l set a E bing and 203'. I' Acidizogen/bbl. l acid	to 11651'. Shut-it to 11651' and circulate tic acid @ 11170 - 113' /2-0.41" holes each @ 111402', 11401', 11406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 12 hr. SITP 3700#. Loaded tubing w/63 bb. set @ 11297'. Perfor 1, 11324', 11326', 11328 aker Model DB packer will set seal assembly in 2 hr. SITP 3000#. Flowed thru Upper Morrow performance of the best of the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the best of the local strue and complete to the loc	n waiting on pipeline of the dock of hole w/258 bbls fresh 70. Pressured casing 11387, 11388, 11389, 11387, 11409, 11411, 11414, OD tubing and a Baker 1 bed dry. Acidized thru SCF Nitrogen/bbl. + 60 00#, AIR 8.3 B/M (5.2 ac 1 lowed 10 BLW + gas © related the Upper Morrow z 8, 11329, 11330, 113 ith a Baker Type "F" pressed 41 BLW/7 hrs + gas © 1 lowed 41 lowed	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'. 1370' with a Baker Lok-set 2 rate of 299 MCFD thru 1" 000 gals 7-1/2% HCl acid age treating press. 5800#,
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' at 12 hr SITP 40%. w/5000 gals 7-1/7500%, formation 4200%, 10 min SI thru 1" choke, Froulled tubing an and 11320', 11321' 11338'. Ran and Ran 2-7/8" OD tupacker set @ 112 choke, FTP 10%. + 1000 SCF Nitro AIR 10.1 B/M (6	le & Lime ned out 10% Ace w zone w 111,00', nd 111115 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer 11322' l set a E bing and 203'. I' Acidizogen/bbl. l acid	PBTD 11651'. Shut-it to 11651' and circulate tic acid @ 11170 - 113' /2-0.41" holes each @ 111402', 111401', 111406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 7500#, min. press. 50 12 hr. SITP 3700#. Loaded tubing w/63 bb: set @ 11297'. Perfor 1, 11321', 11326', 1132 aker Model DB packer will set seal assembly in 2 hr. SITP 3000#. Flowed thru Upper Morrow per Max. press. 6100#, red thru Upper Morrow per Morrow per Max. press. 6100#, red thru Upper Morrow per Morrow per Max. press. 6100#, red thru Upper Morrow per Mo	n waiting on pipeline of the hole w/258 bels fresh 70'. Pressured casing 11387', 11388', 11389', 11409', 11411', 11414' OD tubing and a Baker 10ed dry. Acidized thru SCF Nitrogen/bbl. + 60 00#, AIR 8.3 B/M (5.2 ac 10 fresh water w/2% 12 at 1329', 11330', 113 ith a Baker Type "F" pressed the Upper Morrow z 8', 11329', 11330', 113 ith a Baker Type "F" pressed the BLW/7 hrs + gas 6 at 11320 - 11338' w/50 at 11320' at	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'. 1370' with a Baker Lok-set 2 rate of 299 MCFD thru 1" 000 gals 7-1/2% HCl acid age treating press. 5800#, 10 min SIP 2800#, 15 min March 25, 1976
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' at 12 hr SITP 40%. w/5000 gals 7-1/7500%, formation 4200%, 10 min SI thru 1" choke, Froulled tubing an and 11320', 11321' 11338'. Ran and Ran 2-7/8" OD tupacker set @ 112 choke, FTP 10%. + 1000 SCF Nitro AIR 10.1 B/M (6	le & Lime ned out 10% Ace w zone w 111,00', nd 111115 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer 11322' l set a E bing and 203'. I' Acidizogen/bbl. l acid	PBTD 11651'. Shut-it to 11651' and circulate tic acid @ 11170 - 113' /2-0.41" holes each @ 111402', 111401', 111406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 7500#, min. press. 50 12 hr. SITP 3700#. Loaded tubing w/63 bb: set @ 11297'. Perfor 1, 11321', 11326', 1132 aker Model DB packer will set seal assembly in 2 hr. SITP 3000#. Flowed thru Upper Morrow per Max. press. 6100#, red thru Upper Morrow per Morrow per Max. press. 6100#, red thru Upper Morrow per Morrow per Max. press. 6100#, red thru Upper Morrow per Mo	n waiting on pipeline of the doctor of the waiting on pipeline of the doctor of the waiting on pipeline of the waiting of the waiting of the waiting and a Baker of the waiting and a Baker of the waiting and a Baker of the waiting o	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'. 1370' with a Baker Lok-set 7 rate of 299 MCFD thru 1" 1000 gals 7-1/2% HCl acid age treating press. 5800#, 10 min SIP 2800#, 15 min
T.D. 11690' Shall Drilled and clear spotted 100 gals orated the Morro 11396', 11398', 11440', 11442' at 12 hr SITP 40%. w/5000 gals 7-1/7500%, formation 4200%, 10 min SI thru 1" choke, Froulled tubing an and 11320', 11321' 11338'. Ran and Ran 2-7/8" OD tupacker set @ 112 choke, FTP 10%. + 1000 SCF Nitro AIR 10.1 B/M (6	le & Lime ned out 10% Ace w zone w 111,00', nd 111,15 Swabbed 2% HCl a broke @ P 3600#. TP 15#. d packer 11322' i set a fabing and 203'. I Acidize ogen/bbl. l acid information at the set a fabing and 203'. I acidize ogen/bbl. l acid information at the set a fabing and 203'. I acidize ogen/bbl. l acid information at the set a fabing and 203'. I acidize ogen/bbl. l acid information at the set a fabing and 203'. I acidize ogen/bbl.	PBTD 11651'. Shut-it to 11651' and circulate tic acid @ 11170 - 113' /2-0.41" holes each @ 111402', 111401', 111406'. Ran and set 2-7/8" part of load and swab cid w/additives + 1000 7500#, min. press. 50 12 hr. SITP 3700#. Loaded tubing w/63 bb: set @ 11297'. Perfor 1, 11321', 11326', 1132 aker Model DB packer will set seal assembly in 2 hr. SITP 3000#. Flowed thru Upper Morrow per Max. press. 6100#, red thru Upper Morrow per Morrow per Max. press. 6100#, red thru Upper Morrow per Morrow per Max. press. 6100#, red thru Upper Morrow per Mo	n waiting on pipeline of the hole w/258 bels fresh 70'. Pressured casing 11387', 11388', 11389', 11409', 11411', 11414' OD tubing and a Baker 10ed dry. Acidized thru SCF Nitrogen/bbl. + 60 00#, AIR 8.3 B/M (5.2 ac 10 fresh water w/2% 12 at 1329', 11330', 113 ith a Baker Type "F" pressed the Upper Morrow z 8', 11329', 11330', 113 ith a Baker Type "F" pressed the BLW/7 hrs + gas 6 at 11320 - 11338' w/50 at 11320' at	connection. h water w/2% KCl and then to 1500# - Held O.K. Perf- 11390', 11392', 11394', ', 11435', 11436', 11437', Lok-set packer @ 11297'. Morrow perfs 11387 - 11445' ball sealers. Max. press. cid + 3.1 Nitrogen), ISIP ate of 507.4 MCFD/12 hrs KCl, released packer and one w/2-0.41" holes each 32', 11334', 11336' and ofile nipple @ 11370'. 1370' with a Baker Lok-set 2 rate of 299 MCFD thru 1" 000 gals 7-1/2% HCl acid age treating press. 5800#, 10 min SIP 2800#, 15 min March 25, 1976