

RECEIVED

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY OF LAND MGMT  
ROSWELL DISTRICT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR  
Harvey E. Yates Company

3. ADDRESS OF OPERATOR  
P. O. Box 1933, Roswell, New Mexico 88201

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 1980' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH: Same


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Remedial Work ☐

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐



5. LEASE  
NM-19672

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Pennzoil Federal

9. WELL NO.  
1

10. FIELD OR WILDCAT NAME  
Scanlon Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 32, T-20S, R-29E

12. COUNTY OR PARISH 13. STATE  
Eddy NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3334.4 GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

8/12/83 Run in & set CIBP @ 9690' & dump 35' cmt on top.  
8/18/83 GIH w/196 jts of 4 1/2" 11.6# csg to 6122' KB, cmt w/400 sxs class C w/3/10% CFR-2.  
8/19/83 Run Gamma Ray Cmt Bond Log from 6000' to 3210', TOC-3900'. Perf @ 5430', 5454', 5662', 5700', 5816', 5858', 5891'.  
8/27/83 GIH & set CIBP @ 5380', dump 35' cmt on top, new PBTD 5345'. Perf w/1 spf @ 5262' - 4230', (11 holes).  
9/21/83 Set CIBP @ 4180', dump 35' cmt on top, new PBTD 4145'. Cmt w/255 sx Cl "C" w/6#/sx salt .3 CFR-2.  
9/22/83 Run CBL 3900' - 3210. TOC 3240'.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Raymond J. [Signature] TITLE Res. Engineer DATE December 21, 1983

(This space for Federal or State office use)

APPROVED BY GW [Signature] TITLE \_\_\_\_\_ DATE MAY 8 1984

ROSWELL, NEW MEXICO

\*See Instructions on Reverse Side