

H.M. OIL CONSERVATION COMMISSION

FORM 103 "OTHER"

PAGE # 2 - EXHIBIT "A"

KUYKENDALL COMM # 1 WELL - ROBINSON RESOURCE DEVELOPMENT CO., INC.

PERFORATIONS:

MORROW FORMATION - APRIL 27, 1976 - SCHLUMBERGER

10,117-119-121-122-127-131-132-133-146-148-154-157-199-201.
WITH ONE SHOT PER FOOT, CIRC WITH 140 BBL 3% KCL WATER, SET
RET. BRIDGE PLUG @ 10,219, PRODUCTION PACKER @ 10,191, SPOTTED
WITH 150/ GALS ACIDIC ACID.
TREATED WITH 6000 GALS MS ACID W/NITROGEN

STRAWN FORMATION - MAY 19, 1976 - SCHLUMBERGER

9035,37,38,39 - 9203,04,05.06 - ONE SHOT PER FOOT
9023 - 2 SHOTS PER FOOT.
TREATED W/110 GALS 10% ACIDIC ACID.

5/21/76 - SCHLUMBERGER
9077-78-79; 9135-36-37; 9291-92-93; 9022 & 9023
WITH 0.20" HOLE, ACIDIZED PERF W/5000 GALS 10% ACIDIC ACID.

TREATED ALL PERFS IN STRAWN FORMATION WITH 5000 GALS 15% DS 30

SECOND TREATMENT - PERFS 9036-9206 WITH 5000 GALS 15% DS-30.