

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	✓
U.S.G.S.	
LAND OFFICE	
OPERATOR	

RECEIVED

NEW MEXICO OIL CONSERVATION COMMISSION

JUN 3 1976

O.C.C.
ARTESIA, OFFICE

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. NONE
7. Unit Agreement Name NONE
8. Farm or Lease Name KUYKENDALL COMM.
9. Well No. # 1
10. Field and Pool, or Wildcat WILDCAT
12. County EDDY

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER
2. Name of Operator ROBINSON RESOURCE DEVELOPMENT CO., INC.
3. Address of Operator P.O. Box 1227, ROSWELL, NEW MEXICO 88201
4. Location of Well UNIT LETTER <u>H</u> , <u>1530</u> FEET FROM THE <u>NORTH</u> LINE AND <u>330</u> FEET FROM THE <u>EAST</u> LINE, SECTION <u>18</u> TOWNSHIP <u>21SOUTH</u> RANGE <u>25EAST</u> NMPM.
15. Elevation (Show whether DF, RT, GR, etc.) 3439.2 GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

OTHER ALL PERFS & ELECTRIC LOGS ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

PROPOSE TO PLUG & ABANDON THE ABOVE WELL TO BEGIN JUNE 1, 1976 WITH WORK AS FOLLOWS:

PULL & SHOOT 8300 FEET OF 4-1/2" CASING.
MUD LADEN FLUID WILL BE PLACED BETWEEN PLUGS.
TO SET THE FOLLOWING PLUGS:

#1 @ 10150 W/25 SX CEMENT
2 8900 W/25 SX CEMENT
3 7430 W/35 SX CEMENT
4 5900 W/35 SX CEMENT
5 4560 W/35 SX CEMENT
6 3050 W/35 SX CEMENT
7 2550 W/50 SX CEMENT
8 SURFACE W/15 SX CEMENT.

OTHER: LOGS ATTACHED: DUAL LATERLOG MICRO-SFL; COMPENSATED NEUTRON-FORMATION DENSITY; GAMMA-RAY LOG; BOREHOLE COMPENSATED SONIC LOG.

PERFORATIONS - SEE ATTACHMENT "A"

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED MT Rhine TITLE PRESIDENT DATE 5/28/76

APPROVED BY W. A. Gessett TITLE SUPERVISOR, DISTRICT II DATE JUN 3 1976

CONDITIONS OF APPROVAL, IF ANY: