

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE\*  
(Other instruct on reverse side)Form approved  
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 15003

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Government AB

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Und. Burton Flat Morrow

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 10-T20S-R28E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		RECEIVED	
2. NAME OF OPERATOR Cities Service Oil Company		APR 20 1976	
3. ADDRESS OF OPERATOR Box 1919 - Midland, Texas 79701		O. C. C.	
4. LOCATION OF WELL (Report location clearly and in accordance with any State or Federal law. See also space 17 below.) At surface 1980' FSL & 1980' FWL of Sec. 10-T20S-R28E, Eddy Co., New Mexico		O. C. C.	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3275' GR	12. COUNTY OR PARISH Eddy	13. STATE New Mexico

## 16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data:

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting and proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

T.D. 598' Red Bed & Anhydrite. Prep to drill ahead. This well was spudded @ 12:30 PM on 4-11-76 and drilled to a T.D. of 598'. Ran 12-1/2 Jts. (578.20') 13-3/8" OD 48# H-40 casing set and cemented @ 598' w/625 sacks Class C w/2% CaCl cement. Plug down @ 10:10 AM on 4-12-76. Bumped float w/1450# - Held O.K. Cement did not circulate to surface. WOC 6 hrs. Ran Temp. Survey. Tor of cement @ 105'. Ran 1" tubing in annulus to 83' and pumped in 200 sacks Class C w/2% CaCl cement. Circulated 10 sacks of cement to pit. WOC 14 hrs. Total WOC time of 20 hrs. Tested 13-3/8" casing to 500# - Held O.K.

USGS was notified and witnessed cementing job.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Region Operation Manager

DATE April 14, 1976

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See Instructions on Reverse Side