

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYCOPY
SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 15003

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Government AB

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Und. Burton Flat Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 10-T20S-R28E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER ☐

2. NAME OF OPERATOR
Cities Service Oil Company ✓

3. ADDRESS OF OPERATOR
Box 1919 -- Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)
3275' GR

APR 23 1976

O. C. C.
ARTESIA, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 3005' Sand & Lime. Prep to drill ahead. Drilled to a T.D. of 3000' and ran 12 Jts. (496.42') 8-5/8" OD 32# K-55 and 61-1/3 Jts. (2183.78') 8-5/8" OD 24# K-55 casing set and cemented @ 3000' w/250 sacks Thick Set w/10# Gilsonite and 1/2# Flocele/sack and 2% CaCl followed by 1100 sacks Halliburton Lite w/5# Gilsonite and 1/4# Flocele/sack followed by 300 sacks Class C w/2% CaCl cement. Plug down @ 4:10 PM on 4-18-76. Bumped float w/1500# - Held O.K. Circulated 200 sacks to pit. WOC 27 hrs. Tested 8-5/8" casing to 1500# - Held O.K. Drilled float and cement in 1/2 of shoe ft. and tested to 1500# - Held O.K. Drilled rest of shoe ft. and 5' of new formation to 3005'. RU Halliburton and tested shoe and formation to eq. mud wt. of 10.5#/gal.

USGS was notified and witnessed cementing job.

RECEIVED

APR 21 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Region Operation Manager

DATE April 20, 1976

(This space for Federal or State office use)

TITLE

DATE

APPROVED BY
CONDITIONS OF APPROVAL, IF ANY:

APR 22 1976

M. C. BEEN

ACTING DISTRICT

*See Instructions on Reverse Side