

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE*

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 15003

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Cities Service Oil Company ✓

3. ADDRESS OF OPERATOR

P. O. Box 1919, Midland, Texas 79701

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface
1980' FSL, 1980' FWL of Section 10, Township 20S, Range 28E,
Eddy County, New Mexico

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Government AB

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Und. Burton Flat Morrow

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 10, T20S, R28E

12. COUNTY OR PARISH

Eddy

13. STATE

New Mexico

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3275' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

T.D. 11,400' shale & lime. Waiting on completion unit. This well was drilled to a T.D. of 11,400'. Ran 30 joints (1336.52') of 5 1/2" OD 20# N80 LT&C & 240 joints (9895.25') 5 1/2" OD 17# N80 LT&C casing set & cemented at 11251.57' with 725 sx class H w/.6% CFR-2 & 5# KCI per sack. Plug down at 10:08 A.M., 5-26-76. Bumped float w/3000# - held OK. Ran temp. survey. Top of cement at 8010'.

RECEIVED

JUN 7 1976

O. C. C.
ARTESIA, OFFICE

RECEIVED

JUN - 4 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

JUN 28, 1976

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Region Operation Manager

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

JUN 7 1976

L. L. BEEKMAN
ACTING DISTRICT ENGINEER

*See Instructions on Reverse Side