

July 30, 1976  
Harvey E. Yates Company, Inc.  
Singer-Davis No. 1  
Page 4


July 27, 1976

- 7:00 a.m. - SITP = 3200 psig - 14 hrs.
- 7:10 a.m. - Opened well on 1/2" choke. FTP = 450 psig. 2.9 MMCF/day.
- 10:30 a.m. - Released Well Service Unit. Shut well in for build-up.
- 11:00 a.m. - Released rental equipment from Land & Marine, Davis Tool Company, and Rowland.
- 3:00 p.m. - SITP = 3200 psig - 4 1/2 hrs. Flowed well for 6 hrs. thru 1/2" choke. FTP = 450 psig at 2.9 MMCF/day rate - Flare clean; no water.
- 9:00 p.m. - Shut well in for build-up.
- 12:00 Midnight - SITP = 3110 psig - 3 hrs. shut in.

July 28, 1976

- 7:30 a.m. - SITP = 3150 psig - 10-3/4 hrs. Flowed well thru 1/2" choke for 1 hr. FTP stabilized on 460 psig after 30 min. at 2.96 MMCF/day rate - Flare clean; no water to surface.
- 8:30 a.m. - Shut well in for pressure build-up. Tefteller has been ordered to run CAOF tests on Monday 8/2/76.

Yours very truly,



Peck Hardee, Jr.  
Registered Professional Engineer

PH:ssh  
Attachments:

- 1) Tubing Talley
- 2) 2-Pressure Charts

RECEIVED

NOV 28 1976

G. C. D.  
ANTHONY OFFICE

RECEIVED

10-18-76

OIL COMPANY COMM.  
HOBBS, N. M.

2 2 2 2 2 2 2 2 2 2

2 2 2 2 2 2 2 2 2 2

2 2 2 2 2 2 2 2 2 2