

COPIES RECEIVED	
DISTRIBUTION	
CONTACT	1
FILE	1
S.G.S.	
AND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

NOV - 3 1978

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

C/SF

5a. Indicate Type of Lease
State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.
7. Unit Agreement Name
8. Farm or Lease Name
Singer-Davis
9. Well No.
1
10. Field and Pool, or Wildcat
McMillan Morrow
11. County
Eddy

SUNDY NOTICES AND REPORTS ON WELLS	
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.	
OIL WELL <input type="checkbox"/>	GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>
Name of Operator	
Harvey E. Yates Company	
Address of Operator	
P.O. Box 1933, Roswell, New Mexico 88201	
Location of Well	
UNIT LETTER	K
1980	FEET FROM THE South
LINE AND	1980
FEET FROM	
THE West	LINE, SECTION 7
TOWNSHIP	20S
RANGE	27E
N.M.P.M.	
15. Elevation (Show whether DF, RT, GR, etc.)	3335.8' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
REPAIR OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

This well plugged and abandoned as follows:

Plug No. 1-Top Morrow-25 Sxs class "H" from 10240'-9963' KB.  
 No. 2-Strawn-25 Sxs class "H" from 9105' to 8767' KB.  
 No. 3-Wolfcamp-25 Sxs class "H" from 8000' to 7662' KB.  
 No. 4-Bone Springs-25 Sxs class "H" from 6220' to 5882' KB.  
 No. 5-Cast iron bridge plug @ 5610' KB  
 Shot 4 1/2" csg. off @ 5503' KB W/McCullough Tool Jet Casing Cutter  
 pulled & LD Casing.  
 No. 6-40 Sxs class "H" from 5537' to 5377' KB (in & out 4 1/2" csg. stub)  
 No. 7-40 Sxs class "H" from 2835' to 2695' KB (in & out 3 5/8" csg)  
 No. 8-10 Sxs class "H" @ surface.  
 Intervals between plugs filled w/10 #/gal mud.  
 Installed dry hole marker.  
 P & A 7/1/78.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED	Engineer	DATE	10-31-78
APPROVED BY	SUPERVISOR, DISTRICT II	DATE	SEP 11 1980
CONDITIONS OF APPROVAL, IF ANY:			