## IN M. BL C. C. COFY

## NITED STATES DEPARTMENT OF THE INTERIOR (Other Justice verse side)

GEOLOGICAL SURVEY

STUDIED IN C facate\* Form approved,
Budget Bureau No. 42-R1424.

LEASE DESIGNATION AND SERIAL NO.

	12388-A	
		_
(i 10 t)	COLLAN ALLONGUED OF DESIGNATION AND ADDRESS AND ALLONG	

			H-000-W		
SUNDRY (Do not use this form fo	16. IF INDIAN, ALLOTTE	E OR TRIBE NAME			
i.  OIL GAS WELL WELL X 0	FHER		7. UNIT AGREEMENT N.	AME	
2. NAME OF OPERATOR		3. FARM OR LEASE NA.	ME		
Summit Energy, Inc. V			Flanican F	ed Comm	
3. ADDRESS OF OPERATOR			Flanigan-F	ea. <del>Comm</del>	
112 N. First. 4. LOCATION OF WELL (Report to See also space 17 below.) At surface  2080 * F	10. FIELD AND FOOL, OF ROCKY Arro	yo Wolfcamp			
			Sec. 9-T22S-R22E		
14. PERMIT NO.	15. ELEVATIONS (Show whether	, RT, GR, etc.) 12. COUNTY OR PARISH 13. ST		1 13. STATE	
4386.6 GR			Eddy	N.M.	
16. Che	ck Appropriate Box To Indicate	Nature of Notice, Report, or			
			QUENT REPORT OF:		
TEST WATER SHUT-OFF	PULL OR ALTEE CASING	WATER SHUT-OFF	REPAIRING	WELL	
FRACTURE TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTERING C	ASING	
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONME	NT*	
REPAIR WELL	CHANGE PLANS	(Other) Casing Program X			
(Other)		(Notf: Report result Completion or Recomp	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)		
17. DESCRIBE PROFOSED OR COMPLE proposed work. If we'll is nent to this work.) *	THE OPERATIONS (Clearly state all pertine directionally drilled, srive subsurface loc	ent details, and give pertinent dates rations and measured and true vertic	s, including estimated date cal depths for all marker	te of starting any s and zones perti-	

Tested 13 3/8" casing to 500 psig for 1 hour. Tested o.k. Drilled  $12\frac{1}{4}$ " hole to 1797'. Ran 44 joints 8 5/8" K55 ST&C new casing to 1797'. Cement baskets at 1507, 967, 511. Centralizers at 1755, 1673, 1590. Cemented with 150 sx. Thick Set with 10# Gilsonite/sack + 2% CaCl added; plus 650 sx. Howco Lite with 5# Gilsonite/sx., 4# Flocele/ sx; plus 150 sx. Neat with 2% CaCl. Temp Survey showed cement at 1000' from surface after WOC 6 hours. Ran 1" to 998 and cemented with additional 725 sx. in 12 stages. Completed 4/14/76.

			ARC CENTER
I hereby carries that the foregoing is true and correct			ASTERIAL MENTERS AND THE STREET OF THE STREE
sienes of multiple	TITLE _	Engineer	DATE 4/19/76
This space for Federal or State office use)	TITLE		DATE
CONDITIONS OF APPROVAL, IF ANY:			

\*See Instructions on Reverse Side

X Buh

Sometimes of the state of the s