

OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

**RECEIVED**  
NEW MEXICO OIL CONSERVATION COMMISSION

**JUN 23 1976**

**O. C. C.**  
**ARTESIA, OFFICE**

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease State <input type="checkbox"/> Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No. -----
7. Unit Agreement Name -----
8. Farm or Lease Name Mesa Grande
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat
12. County Eddy

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL ☐ GAS WELL ☒ OTHER- ☐

2. Name of Operator  
Morris R. Antweil

3. Address of Operator  
P. O. Box 2010 Hobbs, New Mexico 88240

4. Location of Well  
UNIT LETTER F 1980 FEET FROM THE North LINE AND 1980 FEET FROM  
THE West LINE, SECTION 11 TOWNSHIP 22-S RANGE 26-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)  
3152' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled 8-3/4" hole to TD 11,550'. Cemented 299 jts. 5-1/2" 17# N-80 LT&C casing at 11,550' with 300 sx Halliburton lite cement containing 5#/sx KCl and 0.6% HALAD-22 and 200 sx Class H cement containing 5#/sx KCl and 0.6% HALAD-22A. Plug down 10:15 AM, 6/20/76. After six hours, ran temperature survey indicating top of cement at 9220' and PBTD 11,510'. Released rig. Casing will be tested prior to beginning completion operations.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R M Wilbourn TITLE Agent DATE 6/21/76

APPROVED BY W A Gussert TITLE SUPERVISOR, DISTRICT II DATE JUN 23 1976

CONDITIONS OF APPROVAL, IF ANY: