

|                        |   |
|------------------------|---|
| NO. OF COPIES RECEIVED | 3 |
| DISTRIBUTION           |   |
| SALE PRICE             | 1 |
| FILE                   | 1 |
| U.S.G.S.               |   |
| LAND OFFICE            |   |
| OPERATOR               | 1 |

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

AUG 23 1976

Form C-101  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

SUNDY NOTICES AND REPORTS ON **O.C.C.**  
**ARTESIA, OFFICE**

(DO NOT USE THIS FORM FOR OPERATIONS TO DRILL OR TO REFINISH OR REPAIR EXISTING RESERVOIR.  
USE MAPS FOR LOCATION FOR OPERATIONS TO DRILL OR TO REFINISH OR REPAIR EXISTING RESERVOIR.)

OIL WELL ☐ GAS WELL ☒ OTHER ☐

Name of Operator  
**Gulf Oil Corporation**

Address of Operator  
**Box 670, Hobbs, New Mexico 88240**

Location of Well  
UNIT LETTER **K**, **1980** FEET FROM THE **South** LINE AND **1980** FEET FROM  
THE **West** LINE, SECTION **26** TOWNSHIP **20-S** RANGE **27-E** N.M.P.M.

15. Elevation (Show whether DF, KT, GR, etc.)  
**3322' GL**

5a. Indicate Type of Lease  
State ☒ Fee ☐

5. State Oil & Gas Lease No.  
**K-6437**

7. Unit Agreement Name

8. Part of Lease Name  
**Eddy FT State**

9. Well No.  
**1**

10. Field and Pool, or Valued  
**Undesignated Morrow**

11. County  
**Eddy**

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐ REMEDIAL WORK ☐ ALTERING CASING ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐ OTHER ☐ CASING TEST AND CEMENT JOBS ☒

OTHER ☐

SUBSEQUENT REPORT OF:

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11,325' TD.

Reached total depth of 7-7/8" hole at 11,325' at 6:30 PM, August 10, 1976. Ran 300 joints and 1 cut joint, 11,308' of 5-1/2" OD 17# N-80 LT&C casing. Set at 11,325' and cemented with 800 sacks of Class H cement containing 1.5% CFR-2, 3# KCL per sack. WOC 8 hours. Temperature survey indicated top of cement at 9720'. WOC over 48 hours. Tested casing with 2,000#, 30 minutes, OK.

RECEIVED

AUG 20 1976

U.S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED **D.F. Berlin** TITLE **Area Engineer** DATE **August 19, 1976**

APPROVED BY **W.A. Gussert** TITLE **SUPERVISOR, DISTRICT II** DATE **AUG 23 1976**

CONDITIONS OF APPROVAL, IF ANY: