

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 no Brazos Rd, Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

C151
B6M
B7M
ST2d

WELL API NO. 30-015-21824
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. L-7010
7. Lease Name or Unit Agreement Name STATE "L"
8. Well No. 1
9. Pool name or Wildcat SWD Delaware

WELL COMPLETION OR RECOMPLETION REPORT AND LOG					
1a. Type of Well: OIL WELL ☐ GAS WELL ☐ DRY ☐ OTHER <u>SWD (Order SWD-610)</u>					
b. Type of Completion: NEW WELL ☐ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DIFF RESVR ☐ OTHER converted P&A well to SWD ☐					
2. Name of Operator DEVON ENERGY CORPORATION (NEVADA)					
3. Address of Operator 20 NORTH BROADWAY, SUITE 1500, OKLAHOMA CITY, OKLAHOMA 73102 (405) 235-3611					
4. Well Location Unit Letter <u>L</u> Feet From The <u>south</u> Line and <u>672</u> Feet From The <u>west</u> Line					
Section <u>10</u> Township <u>21S</u> Range <u>26E</u> NMPM <u>Eddy</u> County					
10. Date Spudded 3/7/96	11. Date T.D. Reached 3/11/96	12. Date Compl. (Ready To Prod.) 3/23/96	13. Elevations (DF, RKB, RT, GR, etc.) GL 3236'	14. Elev. Casinghead	
15. Total Depth, Md & Tvd 4260'	16. Plug, Back T.D. 4206'	17. If Multiple Compl., How Many Zones? N/A	18. Intervals Drilled By	Rotary Tools X	Cable Tools
19. Producing Interval(s), Of This Completion—Top, Bottom, Name SWD intervals: 3980-4130' Delaware					20. Was Directional Survey Made N/A
21. Type Electric And Other Logs Run CBL				22. Was Well Cored No	

23. CASING RECORD (Report all strings set in well)					
CASING SIZE	WEIGHT, LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13 3/8" (existing)	48	455'	17 1/2"	450 sx	
8 5/8" (existing)	24	2594'	12 1/4"	800 sx	
5 1/2" (new)	15.5	4237'	7 7/8"	305 sx H, 50 sx C, 265 sx Poz C,	
				13 3/8" x 8 5/8" ann 5 sx RediMix	
24. LINER RECORD			25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE
					2 7/8"
					3890'
					3903'

26. Perforation record (interval, size and number) 3980-3992' (.40" EHD) w/13 holes Upper Delaware 4024-4048' (.40" EHD) w/25 holes Upper Delaware 4090-4130' (.40" EHD) w/41 holes Lower Delaware	27. ACID SHOT, FRACTURE, CEMENT SQUEEZE, ETC. DEPTH INTERVAL 3980-4048' AMOUNT AND KIND OF MATERIAL USED 2000 gals 7 1/2% NeFe acid + 60 BS 10,000 gals 30# X-Link gel + 14,500 gals 30# Linear gel + 66,000# 16/30 Brady sd + 16,000# 12/20 Brady sd
--	---

28. PRODUCTION							
Date First Production		Productions Method I (Flowing, gas lift, pumping—Size and type of pump)				Well Status (Prod or Shut-In)	
Date Of Test	Hours Tested	Choke Size	Prod'n For Test Period	Oil—Bbl.	Gas—Mcf.	Water—Bbl.	Gas-Oil Ratio
Flow. Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil—Bbl.	Gas—MCF.	Water—Bbl.	Oil Gravity-API (Corr.)	
29. Disposition Of Gas (Sold, Used For Fuel, Vented, Etc.)					Test Witnessed By 6-7-96		
30. List Of Attachments CBL							
31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief							
Signature <i>Gerald T. Pepper</i>			Printed GERALD T. PEPPER		Title DISTRICT ENGINEER Date 4/30/96		

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Northwestern New Mexico

T. Cisco (Bough C)	T. Penn	T. Rustler	T. Penn "A"
T. Wolfcamp	T. Abol	T. Delaware	T. Chinle
T. Drinkard	T. Tubb	T. Cherry Canyon	T. Wingate
T. Bone Springs	T. Sand	T. Entrada	T. Todilto
T. Gr. Wash	T. Ellenburger	T. Morrison	T. Dakota
T. McKee	T. Paddock	T. Base Greenhorn	T. Granite
T. Simpson	T. Glorieta	T. Gallup	T. Ignacio Ozite
T. Montoya	T. San Andres	T. Mancos	T. McCracken
T. Silurian	T. Grayburg	T. Point Lookout	T. Elbert
T. Devonian	T. Queen	T. Menefee	T. Madison
T. Miss	T. 7 Rivers	T. Cliff House	T. Leadville
T. Atoka	T. Yates	T. Pictured Cliffs	T. Penn. "D"
T. Strawn	T. Salt	T. Kirtland-Fruitland	T. Penn. "C"
T. Canyon	T. B. Salt	T. Ojo Alamo	T. Penn. "B"

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1. from	to	feet
No. 2. from	to	feet
No. 3. from	to	feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	DEPTH	(Continued from the front)	Lithology	From	To	Thickness in Feet	Lithology
		4090-4130'	ACID SHOT, FRACTURE 2000 gals 7 1/2% NeFe acid + 75 BS 8000 gals 30# X-Link gel + 12,000 gals 30# Linear gel + 50,000# 16/30 Brady sd + 16,000# 12/20 Brady sd					