

NO. OF COPIES RECEIVED	2
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

RECEIVED

JUL 28 1976

O. C. C.  
ARTEBIA, OFFICE

Form C-103  
Supersedes Old  
C-102 and C-104  
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator BELCO PETROLEUM CORPORATION	8. Farm or Lease Name Jones Comm
3. Address of Operator P. O. Box 19234, Houston, Texas 77024	9. Well No. 1
4. Location of Well UNIT LETTER I 1980 FEET FROM THE south LINE AND 660 FEET FROM THE east LINE, SECTION 9 TOWNSHIP 22 S RANGE 25E NMPM.	10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3520.3	12. County Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☒  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐  
OTHER ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7/20/76 to 7/25/76 Ran & set 56 jnts 9-5/8" csg 36# K-55 ST&C @ 2309'; cmt w/200 scs RFC Class "H" w/12% D-53 + 2% CaCl<sub>2</sub>, followed by 673 scs LightWeight w/5# D-43 + 1/4# Cello flakes/ sc. + 2% CaCl<sub>2</sub>; tailed in w/200 scs Class "C" + 2% CaCl<sub>2</sub>; plug down @ 7:45 a.m. 7/20/76. Cmt not circ; cmt to surface through 1" 300 scs RFC Class "H" w/4% CaCl<sub>2</sub>, 150 scs Class "C" w/2% CaCl<sub>2</sub> & 450 scs BFC w/2-2 Thix set, 5% Kolite w 1/4# seal O Flakes/sc; total cmt 1973 scs; top of cement @ surface WOC time 28 hrs. *(total 16 stages w/ 40% gravel 10% heavy mix + 900 SX cement)*

7/25/76 Drldg cmt and float; pressured tst csg to 1000# spsi; held for 30 min; resumed frm. drilling w/full returns

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Lo. G. Henry TITLE Administrative Geologist DATE 7/26/76

APPROVED BY W. G. Gussitt TITLE SUPERVISOR, DISTRICT II DATE JUL 30 1976

CONDITIONS OF APPROVAL, IF ANY: