

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEYN. M. A. C. C. G. O. R. I.  
(Other Instructions on reverse side)

Budget Bureau No. 42-R1624

5. LEASE DESIGNATION AND SERIAL NO.

NM 26822

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Box Canyon "GJ" Fed.

9. WELL NO. Com

1

10. FIELD AND DEPTH OR WILDCAT

Evident

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 13-21S-21E

Unit 1 NMMPM

12. COUNTY OR PARISH 13. STATE

Eddy

NM

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Yates Petroleum Corporation

3. ADDRESS OF OPERATOR

207 South 4th Street - Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

2130' FSL &amp; 1650' FEL of Sec. 13-21E-21S-21E

AUG 11 1976

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4517' GR

O. C. C.

ARTESIA, OFFICE

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spudded a 17½" hole at 8:00 PM 7-30-76.

TD 1722' - Ran 43 jts of 8-5/8" 24# K-55 new casing (1732.30') of casing set at 1722' KB. 1-Tex. notched shoe, centralizers at 1682 and 805', cement baskets at 840 and 764'. Cemented by Halliburton w/200 sx of thick set followed w/500 sx Lite, 5# gilsonite 1/4# flocele followed w/150 sx Class C 2% CaCl. Cement did not circulate.. PD 6:00 PM 8-3-76. WOC 8 hours & ran Temp. Survey, top of cement at 800' from surface. Stage 1 - Ran 1" to 483', sptd 50 sx of Class C 4% CaCl. PD 4:30 AM 8-4-76. Stage 2 - Ran 1" to 483', sptd 50 sx of Class C 4% CaCl. plus 1 yd of pea gravel. PD 7:45 AM 8-4-76. Stage 3: - Ran 1" to 483' & sptd 50 sx of Class C 4% CaCl plus 1/2 yd of pea gravel. PD 9:45 AM 8-4-76. Stage 4: - Ran 1" to 483' & sptd 50 sx of Class C 4% CaCl plus 1/2 yd pea gravel. PD 12:00 noon 8-4-76. Stage 5: - Ran 1" to 483' & sptd 50 sx of Class C 4% CaCl plus 1/2 yd of pea gravel. PD 3:30 PM 8-4-76. Stage 6: Ran 1" to 483' & sptd 50 sx of Class C 4% CaCl plus 1/2 yd of pea gravel. PD 6:00 PM 8-4-76. Filled to surface. WOC 18 hrs, cut off csg, nipples up, tested BOP's to 1000#. OK. Reduced hole to 7-7/8", drilled plug and tested to 600#. OK. Resumed drilling.

RECEIVED  
AUG-6 1976  
U. S. GEOLOGICAL SURVEY  
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

*Christine Tomlinson*

TITLE

Geol. Secty

DATE

8-6-76

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side