

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	/
FILE	/
U.S.G.S.	
LAND OFFICE	
OPERATOR	/

NEW MEXICO OIL CONSERVATION COMMISSION

AUG 25 1976

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	
7. Unit Agreement Name	
8. Farm or Lease Name South Willow Draw Com	
9. Well No. 1	
10. Field and Pool, or Wildcat West Bubbling Springs	
12. County Eddy	

**SUNDY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-
2. Name of Operator Llano, Inc. ✓
3. Address of Operator P.O. Box 1320, Hobbs, New Mexico 88240
4. Location of Well UNIT LETTER <u>1</u> , <u>990</u> FEET FROM THE <u>east</u> LINE AND <u>1980</u> FEET FROM THE <u>south</u> LINE, SECTION <u>18</u> TOWNSHIP <u>20S</u> RANGE <u>26E</u> NMPM.
15. Elevation (Show whether DF, RT, CR, etc.) 3295.7 GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 12:00 noon MDT, 8/17/76. Set 20" conductor csg @ 30' in 26" hole. Cmdt w/4 yds ready mix. Set 13-3/8"OD 48#H-40 csg @376' in 17½" hole. Cmdt w/300 sx Class "C" containing 2% gel and 2% CaCl followed by 100 sx Class "C" containing 2% CaCl. Plug down @ 7:45 P.M. 8/20/76. Cir 30 sx. to surf. WOC 18 hrs x tested csg to 800 psi, 30 min, ok.

Drilling ahead

Work started: August 17, 1976  
Work completed: August 21, 1976

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. A. Gressett TITLE Manager of Petroleum and Natural Gas Engineering DATE August 24, 1976

APPROVED BY W. A. Gressett TITLE SUPERVISOR, DISTRICT II DATE AUG 25 1976

CONDITIONS OF APPROVAL, IF ANY: