

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE*
(Other instructions on re-
verse side)/Form approved.
Budget Bureau No. 42-R1424.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 14768	
2. NAME OF OPERATOR MONSANTO COMPANY		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR 1330 Midland National Bank Tower, Midland, Texas 79701		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1980' FWL & 1980' FNL, Sec. 10, T-21S, R-27E		8. FARM OR LEASE NAME CERF FEDERAL	
14. PERMIT NO.		9. WELL NO. 2	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3220' Gr.		10. FIELD AND POOL, OR WILDCAT Underlying Burton Flat Morro 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 10, T-21S, R-27E	
		12. COUNTY OR PARISH Eddy	
		13. STATE New Mexico	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Spud

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spudded 17½" hole 9:00 PM 8/10/76.

Drilled 17½" hole to total depth of 596'; Set 13 3/8" 48# H-40 ST&C Casing at 596' and cemented to surface w/ 600 Sx. Lite, 5# Gilsonite, ½# Celloflake, 2% CaCl.

Plug down 5:30 PM 8/12/76.

WOC 24 Hrs & tested w/ 1000 psi for 30 Mins., held OK.

Drilled 12½" hole to total depth of 2860'; Set 9 5/8" 36# K-55 LT&C Casing at 2860'; cemented to surface w/ 1100 Sx. Lite & 100 Sx. Class "C";

Plug down 10:00 AM 8/17/76;

WOC 24 Hrs & tested w/ 1500 psi for 30 Mins., held OK

RECEIVED

AUG 20 1976

U. S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Regional Prod. Mgr.

DATE 8/19/76

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

*See Instructions on Reverse Side