

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER ED
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Bulco Petr. Corp.</u>		Lease <u>Gissler Com.</u>		Well # <u>1</u>	
Location of Well	Unit <u>5</u> <u>21165</u> <u>1650e</u>	Section <u>7</u>	Township <u>21</u>	Range <u>23</u>	County <u>Elddy</u>
Drilling Contractor	<u>McVay</u>		Type of Equipment <u>Rotary 1/2 start approx 9-15-76</u>		

* Witness APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<u>17 1/2"</u>	<u>13 7/8"</u>	<u>48</u>		<u>200</u>	<u>200 lin.</u>
<u>12 1/4"</u>	<u>9 7/8"</u>	<u>36</u>		<u>2200</u>	<u>760 lin.</u>
<u>7 7/8"</u>	<u>5 1/2"</u>	<u>17+20</u>		<u>8900</u>	<u>700</u>

Casing Data:
Int.
 Surface 52 joints of 9 7/8 inch 36 # Grade API New API K-55
 (Approved) (~~Rejected~~)

Inspected by Selan Meernis date 9-22-76

Cementing Program DV Tool 749' Baskets 705-752

Size of hole 12 1/4" Size of Casing 9 7/8 Sacks cement required 950/5x

Type of Shoe used Guide Float collar used Insert Btm 2 jts ~~valued~~ Thread Lock

TD of hole 2230 KB Set 2216' Feet of 9 7/8 Inch 36 # Grade K-55

New-used csg. @ 22 1/2 KB with 200 sacks neat cement around shoe (Class C 2 1/2 cc
 + 4.25 sax Class C 10# Granite 2 1/2 cc additiones Second Stage 325/5x Class C 10# Granite 2 1/2 cc
5K 3% Ecom. Life

Plug down @ 10:00 AM First Stage (AM) (PM) Date 9-23-76
2:45 PM Second Stage

Cement circulated Yes No. of Sacks 35/5x

Cemented by Halliburton Witnessed by Selan Meernis

Temp. Survey ran @ (AM) (PM) Date top cement @

Casing test @ (AM) (PM) Date

Method Used Witnessed by

Checked for shut off @ (AM) (PM) Date

Method used Witnessed by

Remarks: Water 205-30, 535-670, 805-881 Lost Zone 830'
Cut Fell back app. 200' in 30-min Hole will be filled w/Ready Mix.
Surface TD 285 KB 17 1/2" hole Ran 7 jts 13 7/8" 48# A-40 API New
Chat 315/5x Class C 2 1/2 cc PD 1:45 AM 9-17-76 Cn 5/5x