

AMENDED

NEW MEXICO OIL, GAS, AND MINERAL COMMISSION

RECEIVED

JAN 17 1977

Form C-101
Supersedes Old
C-102 and C-103
Effective 1-1-65

DISTRIBUTION	
DATE	
FILE	
RECEIVED	
LAND OFFICE	
OPERATOR	

SUNDY NOTICES AND REPORTS
ARTIFICIAL RESERVOIR

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
BELCO PETROLEUM CORPORATION

3. Address of Operator
10,000 Old Katy Road - Suite #100 Houston, Texas 77055

4. Location of Well
UNIT LETTER **J** **1650** FEET FROM THE **east** LINE AND **2110** FEET FROM
THE **south** LINE, SECTION **7** TOWNSHIP **21-S** RANGE **23-E** N.M.P.M.

5. Elevation (Show whether DF, RT, GR, etc.)
3944.1 Gr

6a. Indicate Type of Lease
Lease ☐ Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Form or Lease Name
Gissler Conn

9. Well No.
1

10. Field and Pool, or Wildcat
Morrow Wildcat

12. County
Eddy

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☒
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☐	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- 11/8/76 Drilled to TD of 8950'; ran Microlaterolog, FDC-CNL-GR Logs.
- 11/11/76 Spotted 35 sx cement plugs 8670-8570', 8290-8190', 7560-7460', 7100-7000', 5400-5300', 4700-4600' for plug back total depth of 4600'.
- 11/12/76 Set 75 sx cement plug 2280-2050'; set 10 sx @ surface; cut off csg.; welded on plate; well plugged and abandoned 11/12/76.
- Mud weight 9.0
13-3/8" csg. set to 285'; left in hole
9-5/8" csg. set to 2230'; left in hole

AMENDED JANUARY 13, 1977, to correct typographical error. Base of plug should be 2280', 50' below base of 9-5/8" casing - left in hole.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *Reo H. King* TITLE **Administrative Geologist** DATE **11/17/76 orig. subm.**

Edgar Thomas

AMENDED 1/4/77