(Rev. 5-63)

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN DUPLICATE (See other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R355.5.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

RECEIVED
MAR 08 1977
U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

RECEIVED
MAR 9 1977
O.C.C.
ARTESIA, OFFICE

5. LEASE DESIGNATION AND SERIAL NO.: 0354232

6. IF INDIAN, ALLOTTEE OR TRIBE NAME:

7. UNIT AGREEMENT NAME:

8. FARM OR LEASE NAME: Elizondo Federal

9. WELL NO.: 3

10. FIELD AND POOL, OR WILDCAT: Burton Flat Morrow

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA: Sec. 20, T-21S, R-27E

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR. ☐ Other

2. NAME OF OPERATOR: Cities Service Oil Company

3. ADDRESS OF OPERATOR: Box 1919, Midland, Texas 79702

4. LOCATION OF WELL (*Report location clearly and in accordance with any State requirements*)
At surface: 660' FSL, 1980' FWL of Section 20, T-21S, R-27E, Eddy County, New Mexico
At top prod. interval reported below: Same as above
At total depth: Same as above

12. COUNTY OR PARISH: Eddy
13. STATE: New Mexico

14. PERMIT NO.	DATE ISSUED

15. DATE SPUDDED	16. DATE T.D. REACHED	17. DATE COMPL. (*Ready to prod.*)	18. ELEVATIONS (DF, RKB, RT, GR, ETC.)*	19. ELEV. CASINGHEAD
11-20-76	12-22-76		3183' GR	3183'

20. TOTAL DEPTH, MD & TVD	21. PLUG, BACK T.D., MD & TVD	22. IF MULTIPLE COMPL., HOW MANY*	23. INTERVALS DRILLED BY	ROTARY TOOLS	CABLE TOOLS
11,690'	11,650'	-	→	0-11,690'	-

24. PRODUCING INTERVAL(S), OF THIS COMPLETION—TOP, BOTTOM, NAME (MD AND TVD)*: 11,381', 11,424' Morrow

25. WAS DIRECTIONAL SURVEY MADE: No

26. TYPE ELECTRIC AND OTHER LOGS RUN: FDCCNL , Gamma Ray Caliper & Dual Laterolog

27. WAS WELL CORED: No

28. CASING RECORD (*Report all strings set in well*)

CASING SIZE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
13 3/8" OD	48	600'	17 ½"	1075 Sacks	None
8 5/8" OD	24 & 32	3000'	12 1/4"	1500 Sacks	None
5 1/2" OD	17 & 20	11,690'	7 7/8"	750 Sacks	None

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)

30. TUBING RECORD

SIZE	DEPTH SET (MD)	PACKER SET (MD)
2 7/8"	11,369.80'	11,364.80'

31. PERFORATION RECORD (*Interval, size and number*)

2 - 0.48" holes per foot at 11,265', 11,267', 11,268', 11272', 11,273', 11,300', 11,346', 11,381',11,399', 11,400', 11,409',11,410', 11,411', 11,414', 11,418', & 11,424'

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
11,265'-11,424'	7000 gals. 7½% acid w/26 RCNCB's & 1000 SCF N2/bbl.
11,381'-11,424'	3500 gals. 7½% MS acid w/1000 SCF N2/bbl. & 22 RCNCB's

33.* PRODUCTION

DATE FIRST PRODUCTION	PRODUCTION METHOD (*Flowing, gas lift, pumping—size and type of pump*)	WELL STATUS (*Producing or shut-in*)
2-14-77	Flowing	Shut in

DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N. FOR TEST PERIOD →	OIL—BBL.	GAS—MCF.	WATER—BBL.	GAS-OIL RATIO
2-26-77	4 hours	8, 10, 13 & 16/64"					

FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE →	OIL—BBL.	GAS—MCF.	WATER—BBL.	OIL GRAVITY-API (CORR.)
1180	-		-0-	1291 (CAOF)	-0-	-

34. DISPOSITION OF GAS (*Sold, used for fuel, vented, etc.*): Well is shut in waiting on pipeline connection.

TEST WITNESSED BY:

35. LIST OF ATTACHMENTS: Deviation Test

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED E. Mulder TITLE Region Operation Mgr. DATE March 2, 1977

*(See Instructions and Spaces for Additional Data on Reverse Side)

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.
If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.
Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.
Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.
Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.
Item 29: *"Sacks Cement":* Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.
Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES

FORMATION	TOP	BOTTOM	DESCRIPTION, CONTENTS, ETC.
NO CORES OR DRILL STEM TESTS TAKEN ON THIS WELL			

38. GEOLOGIC MARKERS

NAME	TOP MEAS. DEPTH	TOP TRUE VERT. DEPTH
Bone Springs	5016'	
Dean	8450'	
Wolfcamp	8694'	
Canyon	9898'	
Strawn	10,184'	
Atoka	10,749'	
Morrow	11,033'	
Chester	11,651'	

* GPO 782-929