

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIP
(Other instruction re-
verse side)Form approved.
Budget Bureau No. 42 R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM03677

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	JAN 18 1977	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR Yates Petroleum Corporation	O.C.C.	8. FARM OR LEASE NAME Stebbins "CQ" Com
3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, NM 88210	ARTESIA, OFFICE	9. WELL NO. 1
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 660' FNL & 1980' FEL of Section 20-20S-29E		10. FIELD AND OR FIELD Undesignated
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3261' GR	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 20-20S-29E 1MPM Unit B
		12. COUNTY OR PARISH Eddy
		13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Set Prod. casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 11906'; PBTD 11872' by wireline. Ran 285 joints of 5½" N-80 20# and 17# LT&C casing (11923.33') set at 11895' KB. 1-Diff-fill up shoe at 11895' and Diff fill up collar at 11850'. Cemented as follows: 250 gallons of mud flush, w/300 sacks of Halli-Lite 5/10% of 1% Hallad-22, CFR2, 5/10 of 1% , 5# KCL. Tailed in w/300 sacks of Class H 5/10% of 1% Hallad 22 and 5# KCL. Displaced w/55 bbls of KCL and 220 bbls of fresh water. PD 4:50 PM 12-28-76. WOC. Tested to 1500#. OK. Ran Temperature Survey and found top of cement at 8390'. PBTD 11872' by wireline.

RECEIVED

JAN 17 1977

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Christine Imbriano

TITLE Geol. Secty

DATE 1-16-77

(This space for Federal or State office use)

APPROVED BY

Joe J. Lora

TITLE

ACTING DISTRICT ENGINEER

DATE

JAN 17 1977

CONDITIONS OF APPROVAL, IF ANY: