

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <i>Citric Service Oil Co.</i>		Lease <i>Tracy E</i>		Well # <i>1</i>	
Location of Well	Unit <i>1880N 660W</i>	Section <i>30</i>	Township <i>21</i>	Range <i>27</i>	County <i>Eddy</i>
Drilling Contractor			Type of Equipment <i>Rotary</i>		

** witness*

APPROVED CASING PROGRAM

Size of Hole	Size of Casing	Weight Per Foot	New or Used	Depth	Sacks Cement
<i>20"</i>	<i>16"</i>	<i>65</i>		<i>400</i>	<i>500 cu</i>
<i>14 3/4"</i>	<i>10 3/4"</i>	<i>40.5</i>		<i>2250</i>	<i>1800 "</i>
<i>8 3/4"</i>	<i>7 5/8"</i>	<i>26-29+33</i>		<i>8850</i>	<i>500</i>
<i>6 1/2"</i>	<i>5" liner</i>	<i>20</i>		<i>8600-11480</i>	

Casing Data:

Surface *57* joints of *10 3/4* inch *40.50* # Grade *20 1/2 10 3/4 40.50 H-40, 37 1/2 10 3/4*
32.75 K-55 (Approved) (~~Rejected~~)

Inspected by *Lelan Mermis* date *12-10-76*

Cementing Program

Size of hole *15 1/2 13 1/2* *14 3/4* TD Size of Casing *10 3/4* Sacks cement required *1700/54*

Type of Shoe used *Guide* Float collar used *Yes* Btm *2* jts welded

TD of hole *2265 KB* Set *2247 1/2* Feet of *10 3/4* Inch *40.5, 32 7/5* Grade *H-40 - K-55*

New-used csg. @ *2247 1/2* with *300* sacks neat cement around shoe (Class C 2% C) + *300 /* sax *Thi set 10 3/4 inch 40.50 2% additives 1100/54 Hovco White 6" 1/2 benite 1/4" Floccle*

Plug down @ *9:30* (AM) (PM) Date *12-10-76*

Cement circulated *Yes* No. of Sacks *60/54*

Cemented by _____ Witnessed by _____

Temp. Survey ran @ _____ (AM) (PM) Date _____ top cement @ _____

Casing test @ _____ (AM) (PM) Date _____

Method Used _____ Witnessed by _____

Checked for shut off @ _____ (AM) (PM) Date _____

Method used _____ Witnessed by _____

Remarks: *4 Cents 2225-2145-2065-1985, 4 Baskets 1450-1490-1530-1570*

Water 105-12, 142-73, 415-22, 545-1263, 1295-1460