

NEW MEXICO OIL CONSERVATION COMMISSION
DRAWER DD
ARTESIA, NEW MEXICO

FIELD REPORT FOR CEMENTING OF WELLS

Operator <u>Plano Inc.</u>		Lease <u>Draw A Com. S. Willow Bottom</u>		Well # <u>1</u>	
Location of Well	Unit <u>2310N 1980E</u>	Section <u>17</u>	Township <u>20</u>	Range <u>26</u>	County <u>Eddy</u>
Drilling Contractor		Type of Equipment <u>Rotary to start approx 12-6-76</u>			
Measurements From KB					
* <u>witness</u> <u>APPROVED CASING PROGRAM</u>					
Size of Hole <u>24"</u>	Size of Casing <u>20"</u>	Weight Per <u>94 Foot</u>	New or Used <u>120</u>	Depth <u>130</u>	Sacks Cement <u>300 c/c</u>
<u>17 1/2"</u>	<u>13 3/8"</u>	<u>48</u>		<u>380</u>	<u>400 "</u>
<u>12 1/4"</u>	<u>8 5/8"</u>	<u>24</u>		<u>1900</u>	<u>700 "</u>
<u>1 7/8"</u>	<u>5 1/2"</u>	<u>15.5+17</u>		<u>10200</u>	
Casing Data:					
Surface <u>55</u> joints of <u>8 5/8</u> inch <u>24</u> # Grade <u>I-55</u>					
<u>Approved ALL</u> (Approved) (Rejected)					
Inspected by <u>Mike Williams</u> date <u>12-19-76</u>					
Cementing Program					
Size of hole <u>12 1/4</u> Size of Casing <u>8 5/8</u> Sacks cement required					
Type of Shoe used <u>None</u> Float collar used <u>Yes</u> Btm 3 jts welded <u>Yes</u>					
TD of hole <u>1906</u> Set <u>1905</u> ^{KB} Feet of <u>8 5/8</u> Inch <u>24</u> # Grade <u>I-55</u>					
<u>New</u> -used csg. @ <u>1905</u> with <u>200</u> sacks neat cement around shoe					
+ <u>600</u> sax <u>Halliburton Light</u> additives <u>5# Gelsinite</u> - <u>1/4# Flo Seal</u> - <u>27% Calcium Chloride</u>					
Plug down @ <u>530</u> (AM) (PM) Date <u>12-19-76</u>					
Cement circulated <u>Yes</u> No. of Sacks <u>65</u>					
Cemented by <u>Halliburton</u> Witnessed by <u>Mike Williams</u>					
Temp. Survey ran @ (AM) (PM) Date top cement @					
Casing test @ (AM) (PM) Date					
Method Used Witnessed by					
Checked for shut off @ (AM) (PM) Date					
Method used Witnessed by					
Remarks: <u>20" Csg Set e 120'</u>					
<u>13 3/8" Csg Set e 345'</u>					
<u>On 8 5/8" Csg Ran 3 Centralizers - 1-60', 1-90', 1-130' off Btm</u>					
<u>Noted Drlg Breaks e 1426-32 + 1435-40</u>					