

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPPLICATE
(Other instructions on reverse side)

Form approved,
Budget Bureau No. 42 R1421.
5. LEASE DESIGNATION AND SERIAL NO.

NM 18605

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)

1. ☐ OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

BELCO PETROLEUM CORPORATION

3. ADDRESS OF OPERATOR

10,000 Old Katy Road - Suite #100, Houston, Texas 77055

4. LOCATION OF WELL (Report location clearly and in accordance with instructions on reverse side. See also space 17 below.)
At surface

1980' FEL, 660' FSL

DEC 15 1976

14. PERMIT NO.

15. ELEVATIONS (Show whether DE, RT, or G.C.C.)

3600 Gr

G.C.C.
ARTESIA, OFFICE

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal RV 4

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Undesignated Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 4, T21S - R25E

12. COUNTY OR PARISH 13. STATE

Eddy

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) spud & casing

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

11/28/76 Spudded 17½" hole.

11/29/76 Drilled to 316'; ran & set 7 jnts 13-3/8" 48# csg @ 316'; cmt'd w/300 sx Class "C" w/2% CaCl₂; circ out 115 sx.

12/5/76 Drilled to 2320'; ran & set 58 jnts 9-5/8" 36# csg @ 2320'; cmt'd w/1000 sx Class "C" w/2% CaCl₂ + 1/4# Celloflakes; tailed in w/200 sx Class "C" w/2% CaCl₂; circ out 250 sx.

12/6/76 Drlg cmt & float collar; tst to 750#; drl'd guide shoe & 5' frm; tst to 200#; resumed frm. drilling.

RECEIVED

DEC 13 1976

U.S. GEOLOGICAL SURVEY
ARTESIA, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

De R. Perry

TITLE Administrative Geologist

DATE 12/9/76

(This space for Federal or State office use)

APPROVED BY

Joe J. Lass

TITLE ACTING DISTRICT ENGINEER

DATE DEC 14 1976

CONDITIONS OF APPROVAL, IF ANY: