(bran 9 53) (May 1963)	DFPART	UNITED STATE	NTERIOR	Other Instruction (Other Instruction verse side)	'IACATE'	Batar approximation Budget Bureau 5. LEASE DESIGNATION 2	1 No. 424 R142	
		E JGICAL SUF		* * *		NM 1126		
(Do not u		ICES AND REPO			E∵D	6. IF INDIAN, ALLOTTEE	OR TRIBE NAM	
1. OIL WELL	7. UNIT AGREEMENT NAME							
2. NAME OF OPEN	8. FARM OR LEASE NAME							
Yates Fetroleum Corporation						NW Indian Basin Unit		
3. ADDRESS OF OPERATOR 207 South 4th Street - Artesia, NMARTSEN OFFICE						9. WELL NO. 1		
 LOCATION OF WELL (Report location clearly and in accordance with any State requirements.⁹ See also space 17 below.) At surface 						10. FIELD AND FOOL, OR WILDCAT Undesignated The anter		
1885' FSL & 208 0 ' FWL of Section 12-218-22E						11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec., 12-21S-22E Unit K NMPM		
14. PERMIT NO.		15. ELEVATIONS (Show whether DF, RT, GR, etc.)			12. COUNTY OR PARISH 13. STATE			
		4107	GR			Eddy	NM	
16.	Check Ap	opropriate Box To In	dicate Natu	e of Notice, Rep	oort, or C	Other Data		Å
NOTICE OF INTENTION TO: SUBSEQU						ENT REPORT OF:		
TEST WATER Fracture te Bhoot or ac		PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON*	x	WATER SHUT-OFF Fracture treatm Shooting or acid		REPAIRING W ALTERING CA ABANDONMEN	81NG	
REPAIR WELI (Other)	BEFAIR WELL CHANGE PLANS (Other) (Other) (Note: Report n Completion or R					sults of multiple completion on Well ompletion Report and Log form.)		
17. DESCRIBE PRO proposed w nent to this	ork. If well is direction	RATIONS (Clearly state a maily drilled, give subs	ll pertinent des rface locations	ails, and give pertir and measured and t	ient dates, rue vertica	including estimated date l depths for all markers	of starting a and zones per	ny rti-

TD 1750' - Well was drilled to 1750'. Stuck 8-5/8" casing at 623' while attempting to run casing. Recovered 542' of 8-5/8" casing, unable to pull last two joints. Washed 7-7/8" hole outside of casing to 700' and will spot 370 sacks of Class "C" cement 4% CaCl w/3#/sx 20-40 sand at 700-300', spot 110 sx Class C cement 2% CaCl at 120' to surface, cemen dropped, will fill hole w/5 yards of Ready-mix. The rig will be skidded 20' to the west and re-drill well.

RECEIVEL DEC 22 1976

U.S. GEOLOGICAL SURVE ARTESIA, NEW MEXICO 18. I here 12-21-76 Engineer DATE _ TTTLE SIGN (This space for Federal TITLE ACTING DISTRICT ENGINEER DATE DEC 9 APPROVED BY CONDITIONS OF APPROVAL, IF ANY: eren er Freisen Freisen Freisen

*See Instructions on Reverse Side

.

.